



产品系列
PRODUCTS SERIES

型号	MR18TBW100	MR18TBX100	MR18-8A	MR18-600F
Nominal Diameter	460mm/18 inch	460mm/18 inch	460mm/18inch	460mm/18 inch
Nominal Impedance	8Ω	8Ω	8Ω	8Ω
AES Power Handling	900W	800W	800W	800W
Sensitivity 1W/1M	95.6dB	95.2dB	95.8dB	95.1dB
Frequency Range	40-1.8KHz	34-2.6KHz	40.3-1.5KHz	37-3.4KHz
Voice Coil Diameter	100mm/4 inch	100mm/4 inch	100mm/4 inch	100mm/4 inch
Magnet	Φ220 Ferrite Ring	Φ220 Ferrite Ring	Φ220 Ferrite Ring	Φ220 Ferrite Ring

型号	MR18-8D	MR18-15B	MR18-15BS	MR18-5D
Nominal Diameter	460mm/18 inch	460mm/18inch	460mm/18 inch	460mm/18 inch
Nominal Impedance	8Ω	8Ω	8Ω	8Ω
AES Power Handling	1000W	750W	800W	750W
Sensitivity 1W/1M	92.1dB	95.8dB	96.4dB	94.5dB
Frequency Range	38.1-1.3KHz	39.2Hz-2.8kHz	38-2.3KHz	41.3-2.6kHz
Voice Coil Diameter	115mm/4.5 inch	100mm/4 inch	100mm/4 inch	100mm/4 inch
Magnet	Φ220 Ferrite Ring	Φ220 Ferrite Ring	Φ220 Ferrite Ring	Φ220 Ferrite Ring

型号	MR18G401	MR18P400	MR18P300	MR18250115R
Nominal Diameter	460mm/18inch	460mm/18 inch	460mm/18inch	460mm/18 inch
Nominal Impedance	8Ω	8Ω	8Ω	8Ω
AES Power Handling	750W	500W	750W	1000W
Sensitivity 1W/1M	96.4dB	92.6dB	96dB	93.7dB
Frequency Range	96-2.5kHz	38-2.5KHz	39.6-3.4KHz	41-2.1KHz
Voice Coil Diameter	100mm/4 inch	100mm/4 inch	100mm/4 inch	115mm/4.5 inch
Magnet	Φ220 Ferrite Ring	Φ220 Ferrite Ring	Φ220 Ferrite Ring	Φ253 Ferrite Ring

型号	MR280-1	MR1850-A	MR280125	MR18-29B
Nominal Diameter	460mm/18inch	460mm/18 inch	460mm/18 inch	460mm/18 inch
Nominal Impedance	8Ω	8Ω	8Ω	8Ω
AES Power Handling	1200W	1200W	1200W	1200W
Sensitivity 1W/1M	96dB	95.5dB	97dB	94dB
Frequency Range	44-2.2kHz	38-1.9KHz	42.5-1.8KHz	36-2.2KHz
Voice Coil Diameter	125mm/5 inch	125mm/5inch	125mm/5 inch	125mm/5 inch
Magnet	Φ280 Ferrite Ring	Φ280 Ferrite Ring	Φ280 Ferrite Ring	Φ280 Ferrite Ring

型号	MR18-33A	MR18300150S	MR18300150BS	MR18N401
Nominal Diameter	460mm/18 inch	460mm/18 inch	460mm/18 inch	460mm/18 inch
Nominal Impedance	4Ω	8Ω	8Ω	8Ω
AES Power Handling	1200W	1500W	1600W	800W
Sensitivity 1W/1M	92.7dB	94dB	96.8dB	98.2dB
Frequency Range	36-1.8KHz	48-900kHz	56-900kHz	37-2.3kHz
Voice Coil Diameter	125mm/5 inch	152mm/6 inch	152mm/6 inch	100mm/4 inch
Magnet	Φ280 Ferrite Ring	Φ300 Ferrite Ring	Φ300 Ferrite Ring	Neodymium Ring

型号	MR18SW100	MR18SW115	MR21-2	MR21SW001A-01
Nominal Diameter	460mm/18 inch	460mm/18 inch	530mm/21inch	550mm/21inch
Nominal Impedance	8Ω	8Ω	8Ω	8Ω
AES Power Handling	800W	1000W	2000W	1000W
Sensitivity 1W/1M	97dB	95.7dB	96.6dB	96dB
Frequency Range	42.1-2.5KHz	30.4-1.3kHz	27-1.5kHz	30-1.8kHz
Voice Coil Diameter	100mm/4 inch	115mm/4.5 inch	150mm/6 inch	152.4mm/6 inch
Magnet	Neodymium Ring	Neodymium Ring	Ferrite Ring	Neodymium Ring

型号	MR06H13-34T	MR08H13-34T	MR08HF06A-01	MR10H13-44T
Nominal Diameter	165mm/6.5 inch	200mm/8 inch	200mm/8 inch	254mm/10 inch
Nominal Impedance	8Ω	8Ω	8Ω	8Ω
AES Power Handling	250W	250W	150W	250W
Sensitivity 1W/1M	93.4dB	92dB	97dB	91.4dB
Frequency Range	113-2.6KHz	85-20KHz	68-5.2kHz	58.4-6.2KHz
Voice Coil Diameter	52mm/2 inch	50mm/2 inch	50mm/2 inch	65mm/2.6inch
Magnet	Neodymium Ring	Φ145 Ferrite Ring	Φ156 Ferrite Ring	Φ156 Ferrite Ring

型号	MR12H13-44T	MR12H12-44T	MR12N76-75T	MR15-9T
Nominal Diameter	300mm/12 inch	300mm/12 inch	300mm/12 inch	380mm/15 inch
Nominal Impedance	8Ω	8Ω	8Ω	8Ω
AES Power Handling	300W	300W	400W	500W
Sensitivity 1W/1M	93dB	97dB	98dB	91.1dB
Frequency Range	53-5.5KHz	48-5kHz	45-18KHz	30-3.7KHz
Voice Coil Diameter	75mm/3inch	75.5mm/3 inch	76mm/3inch	75mm/3 inch
Magnet	Φ180 Ferrite Ring	Φ190 Ferrite Ring	Neodymium Ring	Φ190 Ferrite Ring

型号	MR15H13-44T	MR15N76-75T	MR80-1	MR350S
Nominal Diameter	380mm/15 inch	380mm/15 inch	25mm/1 inch	25mm/1 inch
Nominal Impedance	8Ω	8Ω	8Ω	8Ω
AES Power Handling	350W	400W	25W	80W
Sensitivity 1W/1M	93.3dB	98dB	107dB	105dB
Frequency Range	43-18KHz	49.5-18KHz	800-16kHz	800-18kHz
Voice Coil Diameter	75mm/3inch	75mm/3inch	25mm/1 inch	44mm/1.7 inch
Magnet	Φ180 Ferrite Ring	Neodymium Ring	Ferrite Ring	Ferrite Ring

型号	MR340S	MR440T	MR440S	MR440F
Nominal Diameter	25mm/1 inch	25mm/1 inch	25mm/1 inch	25mm/1 inch
Nominal Impedance	8Ω	8Ω	8Ω	8Ω
AES Power Handling	30W	60W	60W	60W
Sensitivity 1W/1M	107.5dB	108.5dB	105dB	102dB
Frequency Range	1000-17kHz	1k-18kHz	650-16kHz	650-16kHz
Voice Coil Diameter	34mm/1.3 inch	44mm/1.7 inch	44mm/1.7 inch	44mm/1.7 inch
Magnet	Ferrite Ring	Ferrite Ring	Ferrite Ring	Ferrite Ring

型号	MR44G	MR45G	MR44TW03A-01	MR44TW04A-01
Nominal Diameter	25mm/1 inch	25mm/1 inch	25mm/1 inch	25mm/1 inch
Nominal Impedance	8Ω	8Ω	8Ω	8Ω
AES Power Handling	40W	60W	40W	60W
Sensitivity 1W/1M	107dB	108.5dB	107dB	108.5dB
Frequency Range	800-18kHz	1k-18kHz	1.5k-18kHz	700-18kHz
Voice Coil Diameter	44mm/1.7 inch	44mm/1.7 inch	44mm/1.7 inch	44mm/1.7 inch
Magnet	Ferrite Ring	Ferrite Ring	Ferrite Ring	Ferrite Ring

型号	MR51-1	MR51-5	MR610	MR450
Nominal Diameter	25mm/1 inch	25mm/1 inch	38mm/1.5 inch	25mm/1 inch
Nominal Impedance	8Ω	8Ω	8Ω	8Ω
AES Power Handling	70W	70W	110W	60W
Sensitivity 1W/1M	108dB	108dB	109dB	107dB
Frequency Range	800-17kHz	800-20kHz	800-18kHz	800-18kHz
Voice Coil Diameter	51mm/2 inch	51mm/2 inch	65mm/2.5 inch	44mm/1.7 inch
Magnet	Ferrite Ring	Ferrite Ring	Ferrite Ring	Ferrite Ring

型号	MR750A	MR72-6	MR750S	MR75-5
Nominal Diameter	38mm/1.5 inch	38mm/1.5 inch	38mm/1.5 inch	38mm/1.5 inch
Nominal Impedance	8Ω	8Ω	8Ω	8Ω
AES Power Handling	110W	110W	110W	110W
Sensitivity 1W/1M	107.5dB	107dB	107.5dB	107.5dB
Frequency Range	800-16kHz	800-16kHz	600-18kHz	800-18kHz
Voice Coil Diameter	72mm/2.8 inch	72mm/2.8 inch	72mm/2.8 inch	75mm/3 inch
Magnet	Ferrite Ring	Ferrite Ring	Ferrite Ring	Ferrite Ring

型号	MR75-9	MR75TW03A-01	MR850	MR44XT
Nominal Diameter	38mm/1.5 inch	38mm/1.5 inch	50mm/2 inch	50mm/2 inch
Nominal Impedance	8Ω	8Ω	8Ω	8Ω
AES Power Handling	80W	200W	110W	140W
Sensitivity 1W/1M	107.5dB	102dB	108.5dB	109dB
Frequency Range	800-18kHz	1500-18K Hz	600-18kHz	1000-18kHz
Voice Coil Diameter	75mm/3 inch	75mm/3inch	75mm/3 inch	100mm/4 inch
Magnet	Ferrite Ring	Ferrite Ring	Neodymium Ring	Ferrite Ring

型号	MR100	MR350T	MR2409	MR350
Nominal Diameter	50mm/2 inch	25mm/1 inch	25mm/1 inch	25mm/1 inch
Nominal Impedance	8Ω	8Ω	8Ω	8Ω
AES Power Handling	140W	30W	30W	60W
Sensitivity 1W/1M	107dB	106dB	108.5dB	105dB
Frequency Range	1000-18kHz	1000-15kHz	1000-18kHz	800-18kHz
Voice Coil Diameter	100mm/4 inch	36mm/1.4 inch	36mm/1.4 inch	44mm/1.7 inch
Magnet	Ferrite Ring	Neodymium Ring	Neodymium Ring	Ferrite Ring

型号	MR400	MR44TW950A-01	MR500	MR650N
Nominal Diameter	25mm/1 inch	26mm/1 inch	25mm/1 inch	38mm/1.5 inch
Nominal Impedance	8Ω	8Ω	8Ω	8Ω
AES Power Handling	60W	70W	60W	90W
Sensitivity 1W/1M	107dB	102dB	108dB	110dB
Frequency Range	800-17kHz	1500-19K Hz	800-19kHz	700-20kHz
Voice Coil Diameter	44mm/1.7 inch	65mm/2.6inch	44mm/1.7 inch	63.7mm/2.5 inch
Magnet	Neodymium Ring	Ferrite Ring	Neodymium Ring	Neodymium Ring

型号	MR64TW950A-01	MR75TW950A-01	MR800	MR900
Nominal Diameter	38mm/1.5 inch	38mm/1.5 inch	38mm/1.5 inch	38mm/1.5 inch
Nominal Impedance	8Ω	8Ω	8Ω	8Ω
AES Power Handling	70W	70W	110W	110W
Sensitivity 1W/1M	96dB	101dB	107.5dB	108.5dB
Frequency Range	710K-20K Hz	650-18kHz	500-18kHz	800-19kHz
Voice Coil Diameter	65mm/2.6inch	75mm/3inch	75mm/3 inch	75mm/3 inch
Magnet	Ferrite Ring	Ferrite Ring	Neodymium Ring	Ferrite Ring



MERRY AUDIO

FOR PROFESSIONAL AUDIO
VOCALIZATION

