

PROFESSIONAL
SPEAKER
SERIES



MERRY AUDIO

HF DRIVER

高音喇叭系列

LF DRIVER

低音喇叭系列

COAXIAL

同轴喇叭系列

LINE ARRAY

线阵喇叭系列

专业OEM/ODM定制源头厂家

Professional Speakers OEM/ODM Manufacturer



ABOUT US

Meirui (Guangdong) Audio Equipment Co., Ltd.

20 Years

Professional loudspeaker manufacturer

40 Patents

Innovative and patented technologies

40,000 m²

Square meters of production base

10,000 Daily Output


Commercial speaker daily output

COMPANY PROFILE


Founded in 2005, Merry Audio is a professional manufacturer focusing on R&D, manufacturing and sales of high-power speakers for entertainment KTV, bars, conferences and outdoor performances. We are committed to providing our customers with high-quality speaker units and supporting solutions.



WITH AN AREA OF
40,000 SQUARE METERS OF
PRODUCTION BASE



Corporation have
KLIPPEI, LMS, CLIO
laser testing elastic wave
displacement and
drum paper
FS instrument



Merry Audio is able to meet the individual needs for various **OEM** and **ODM** services!

The complete **IATF16949** and **ISO9001** quality management system and efficient executive team have made Merry Audio been favored by plenty of customers for many years.





DIRECTORY

2 / 3 / 4 INCH	-----	P03-04
5 / 6 / 8 INCH	-----	P05-06
10 INCH	-----	P07-09
12 INCH	-----	P10-15
15 INCH	-----	P16-22
18 INCH	-----	P23-28
21 INCH	-----	P29
IRON BASKET 4-18"	-----	P30-33
COAXIAL	-----	P34
CAR SPEAKER	-----	P35-36
HF DRIVERS	-----	P37-41
VOICE COIL / CROSSOVERS / COMPRESSION DRIVER HORNS	-----	P42



MR02N01

Nominal Diameter	标准直径:	67mm/2.5inch
Nominal Impedance	标称阻抗:	4Ω
AES Power Handling	AES功率:	20W (AES)
Maximum Power	最大功率:	35W
Sensitivity 1W/1M	灵敏度:	88dB
Frequency Range	频响范围:	184-20k Hz
Voice Coil Diameter	音圈直径:	20mm/0.8inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Neodymium ring



MR02N03

Nominal Diameter	标准直径:	67mm/2.5inch
Nominal Impedance	标称阻抗:	4Ω
AES Power Handling	AES功率:	20W (AES)
Maximum Power	最大功率:	40W
Sensitivity 1W/1M	灵敏度:	90dB
Frequency Range	频响范围:	183-20k Hz
Voice Coil Diameter	音圈直径:	20mm/0.8inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Neodymium ring



MR65T01C-A

Nominal Diameter	标准直径:	74.7mm/3 inch
Nominal Impedance	标称阻抗:	2Ω
AES Power Handling	AES功率:	10W
Maximum Power	最大功率:	15W
Sensitivity 1W/1M	灵敏度:	99dB
Frequency Range	频响范围:	900K~15K Hz
Voice Coil Diameter	音圈直径:	13mm/0.5inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Φ55Ferrite Ring/H9mm



MR75T01C-A

Nominal Diameter	标准直径:	98mm/3 inch
Nominal Impedance	标称阻抗:	4Ω
AES Power Handling	AES功率:	15W
Maximum Power	最大功率:	20W
Sensitivity 1W/1M	灵敏度:	104dB
Frequency Range	频响范围:	11-17K Hz
Voice Coil Diameter	音圈直径:	14mm/0.56inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ50/55Ferrite Ring/H10/8mm



MR03F08C

Nominal Diameter	标准直径:	81mm/3inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	20W (AES)
Maximum Power	最大功率:	40W
Sensitivity 1W/1M	灵敏度:	91dB
Frequency Range	频响范围:	104-20kHz
Voice Coil Diameter	音圈直径:	19mm/0.76 inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Φ72Ferrite Ring/H15mm



MR03F09C

Nominal Diameter	标准直径:	83mm/3 inch
Nominal Impedance	标称阻抗:	4Ω
AES Power Handling	AES功率:	20W (AES)
Maximum Power	最大功率:	40W
Sensitivity 1W/1M	灵敏度:	86dB
Frequency Range	频响范围:	103-6.5kHz
Voice Coil Diameter	音圈直径:	19.4mm/0.76 inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ70Ferrite Ring/H15mm



MR03F15C

Nominal Diameter	标准直径:	79mm/3 inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	20W (AES)
Maximum Power	最大功率:	40W
Sensitivity 1W/1M	灵敏度:	90dB
Frequency Range	频响范围:	131-20kHz
Voice Coil Diameter	音圈直径:	20mm/0.8 inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Φ65Ferrite Ring/H15mm

Fiber



MR03F18C

Nominal Diameter	标准直径:	96mm /3inch
Nominal Impedance	标称阻抗:	4Ω
AES Power Handling	AES功率:	40W (AES)
Maximum Power	最大功率:	80W
Sensitivity 1W/1M	灵敏度:	87dB
Frequency Range	频响范围:	130-19k Hz
Voice Coil Diameter	音圈直径:	20mm / 0.8inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ65Ferrite Ring/H15mm



MR03N01

Nominal Diameter	标准直径:	73mm/3inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	20W (AES)
Maximum Power	最大功率:	35W
Sensitivity 1W/1M	灵敏度:	90dB
Frequency Range	频响范围:	130-20k Hz
Voice Coil Diameter	音圈直径:	19.4mm/0.75inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Neodymium Ring



MR03N02C

Nominal Diameter	标准直径:	81mm/3inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	20W (AES)
Maximum Power	最大功率:	40W
Sensitivity 1W/1M	灵敏度:	91dB
Frequency Range	频响范围:	110-20kHz
Voice Coil Diameter	音圈直径:	19mm/0.76 inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Neodymium ring

Fiber



MR04F08C

Nominal Diameter	标准直径:	112mm/4inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	30W (AES)
Maximum Power	最大功率:	60W
Sensitivity 1W/1M	灵敏度:	91dB
Frequency Range	频响范围:	108-20k Hz
Voice Coil Diameter	音圈直径:	19mm/0.75inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Φ72Ferrite Ring/H15mm

Fiber



MR04F50A

Nominal Diameter	标准直径:	106mm/4inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	40W (AES)
Maximum Power	最大功率:	70W
Sensitivity 1W/1M	灵敏度:	90dB
Frequency Range	频响范围:	114-20k Hz
Voice Coil Diameter	音圈直径:	25mm/1inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Φ80Ferrite Ring/H15mm



MR04F43C

Nominal Diameter	标准直径:	120mm / 4 inch
Nominal Impedance	标称阻抗:	4Ω
AES Power Handling	AES功率:	40W (AES)
Maximum Power	最大功率:	80W
Sensitivity 1W/1M	灵敏度:	88dB
Frequency Range	频响范围:	97-16k Hz
Voice Coil Diameter	音圈直径:	16mm / 0.6 inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ80Ferrite Ring/H15mm



MR04F30C

Nominal Diameter	标准直径:	112mm/4inch
Nominal Impedance	标称阻抗:	4Ω
AES Power Handling	AES功率:	25W (AES)
Maximum Power	最大功率:	45W
Sensitivity 1W/1M	灵敏度:	88dB
Frequency Range	频响范围:	98-16kHz
Voice Coil Diameter	音圈直径:	19mm/0.75 inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Φ72Ferrite Ring/H15mm



MR04F35C

Nominal Diameter	标准直径:	105mm/4inch
Nominal Impedance	标称阻抗:	6Ω
AES Power Handling	AES功率:	20W (AES)
Maximum Power	最大功率:	40W
Sensitivity 1W/1M	灵敏度:	87dB
Frequency Range	频响范围:	152-15kHz
Voice Coil Diameter	音圈直径:	20mm/0.8 inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Φ70Ferrite Ring/H15mm



MR04F55C-A

Nominal Diameter	标准直径:	123mm / 4inch
Nominal Impedance	标称阻抗:	4Ω
AES Power Handling	AES功率:	50W (AES)
Maximum Power	最大功率:	100W
Sensitivity 1W/1M	灵敏度:	90dB
Frequency Range	频响范围:	71-8k Hz
Voice Coil Diameter	音圈直径:	25mm /1inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ80Ferrite Ring/H15mm



MR04F15A-A

Nominal Diameter	标准直径:	103mm/4inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	30W (AES)
Maximum Power	最大功率:	60W
Sensitivity 1W/1M	灵敏度:	87dB
Frequency Range	频响范围:	80-10kHz
Voice Coil Diameter	音圈直径:	25mm/1 inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ80Ferrite Ring/H15mm



MR04F02C-A

Nominal Diameter	标准直径:	118mm/4inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	40W (AES)
Maximum Power	最大功率:	80W
Sensitivity 1W/1M	灵敏度:	86dB
Frequency Range	频响范围:	86-10.7kHz
Voice Coil Diameter	音圈直径:	25mm/1 inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ80Ferrite Ring/H15mm



MR04F19C

Nominal Diameter	标准直径:	105mm/4inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	40W (AES)
Maximum Power	最大功率:	80W
Sensitivity 1W/1M	灵敏度:	88dB
Frequency Range	频响范围:	100-18kHz
Voice Coil Diameter	音圈直径:	25mm/1 inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ85Ferrite Ring/H15mm



MR45F03

Nominal Diameter	标准直径:	123mm/4.5inch
Nominal Impedance	标称阻抗:	4Ω
AES Power Handling	AES功率:	30W (AES)
Maximum Power	最大功率:	60W
Sensitivity 1W/1M	灵敏度:	90dB
Frequency Range	频响范围:	61-10.0kHz
Voice Coil Diameter	音圈直径:	32mm/1.27 inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Φ90Ferrite Ring/H20mm



MR45F01

Nominal Diameter	标准直径:	112mm/4.5inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	30W (AES)
Maximum Power	最大功率:	60W
Sensitivity 1W/1M	灵敏度:	92dB
Frequency Range	频响范围:	110-18kHz
Voice Coil Diameter	音圈直径:	25mm/1 inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Φ90Ferrite Ring/H18mm



MR04N08C

Nominal Diameter	标准直径:	112mm/4.5inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	30W (AES)
Maximum Power	最大功率:	60W
Sensitivity 1W/1M	灵敏度:	90dB
Frequency Range	频响范围:	100-20k Hz
Voice Coil Diameter	音圈直径:	19.4mm/0.75inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Neodymium Ring



MR45N02C

Nominal Diameter	标准直径:	112mm/4.5inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	50W (AES)
Maximum Power	最大功率:	100W
Sensitivity 1W/1M	灵敏度:	95dB
Frequency Range	频响范围:	110-18kHz
Voice Coil Diameter	音圈直径:	25mm/1 inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Neodymium ring



MR04N03C

Nominal Diameter	标准直径:	115mm/4.5inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	40W (AES)
Maximum Power	最大功率:	80W
Sensitivity 1W/1M	灵敏度:	91dB
Frequency Range	频响范围:	145-20kHz
Voice Coil Diameter	音圈直径:	25mm/1 inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Neodymium Ring



MR05H42C

Nominal Diameter	标准直径:	135mm /5 inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	100W (AES)
Maximum Power	最大功率:	200W
Sensitivity 1W/1M	灵敏度:	95dB
Frequency Range	频响范围:	120-13k Hz
Voice Coil Diameter	音圈直径:	35mm /1.5 inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Φ120Ferrite Ring/H20mm



MR06H06A

Nominal Diameter	标准直径:	153mm/6inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	100W (AES)
Maximum Power	最大功率:	200W
Sensitivity 1W/1M	灵敏度:	93dB
Frequency Range	频响范围:	130-8KHz
Voice Coil Diameter	音圈直径:	38mm/1.5 inch
Winding Material	线材:	Copper-clad aluminium wire
Magnet	磁体:	Φ120Ferrite Ring/H20mm



MR06H91C

Nominal Diameter	标准直径:	162mm/6.5inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	100W (AES)
Maximum Power	最大功率:	200W
Sensitivity 1W/1M	灵敏度:	95dB
Frequency Range	频响范围:	86-8.5k Hz
Voice Coil Diameter	音圈直径:	38mm/1.5inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Φ120Ferrite Ring/H20mm



MR06N18E

Nominal Diameter	标准直径:	162mm/6.5inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	120W (AES)
Maximum Power	最大功率:	240W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	85-7.5k Hz
Voice Coil Diameter	音圈直径:	38mm/1.5inch
Winding Material	线材:	Copper
Magnet	磁体:	Neodymium Ring



MR06N89C

Nominal Diameter	标准直径:	162mm/6.5inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	150W (AES)
Maximum Power	最大功率:	300W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	95-9k Hz
Voice Coil Diameter	音圈直径:	50mm/2inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Neodymium Ring



MR06N18D

Nominal Diameter	标准直径:	161/6.5inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	150W (AES)
Maximum Power	最大功率:	300W
Sensitivity 1W/1M	灵敏度:	98dB
Frequency Range	频响范围:	132-6k Hz
Voice Coil Diameter	音圈直径:	51mm/2 inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Neodymium Ring



MR06H08

Nominal Diameter	标准直径:	162mm/6.5 inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	150W (AES)
Maximum Power	最大功率:	300W
Sensitivity 1W/1M	灵敏度:	95dB
Frequency Range	频响范围:	69-7k Hz
Voice Coil Diameter	音圈直径:	51mm/2 inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Neodymium Ring



MR08H29D

Nominal Diameter	标准直径:	210mm/8inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	150W (AES)
Maximum Power	最大功率:	300W
Sensitivity 1W/1M	灵敏度:	95dB
Frequency Range	频响范围:	68-6k Hz
Voice Coil Diameter	音圈直径:	50mm/2inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ135Ferrite Ring/H20mm



MR08H02D

Nominal Diameter	标准直径:	210mm/8inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	150W (AES)
Maximum Power	最大功率:	300W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	65-5.2k Hz
Voice Coil Diameter	音圈直径:	51mm/2 inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ140Ferrite Ring/H20mm



MR08H37D

Nominal Diameter	标准直径:	210mm/8inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	150W (AES)
Maximum Power	最大功率:	300W
Sensitivity 1W/1M	灵敏度:	95dB
Frequency Range	频响范围:	65-7k Hz
Voice Coil Diameter	音圈直径:	50mm/2inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ135Ferrite Ring/H20mm



MR08H38D

Nominal Diameter	标准直径:	210mm/8inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	200W (AES)
Maximum Power	最大功率:	400W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	70-7k Hz
Voice Coil Diameter	音圈直径:	50mm/2inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ140*2Ferrite Ring/H20*2mm



MR08H28D-A

Nominal Diameter	标准直径:	210mm/8 inch
Nominal Impedance	标称阻抗:	16Ω
AES Power Handling	AES功率:	250W (AES)
Maximum Power	最大功率:	500W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	77-5k Hz
Voice Coil Diameter	音圈直径:	65mm/2.5 inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ156Ferrite Ring/H20mm

**MR08H90**

Nominal Diameter	标准直径 :	210mm/8inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	120W (AES)
Maximum Power	最大功率 :	240W
Sensitivity 1W/1M	灵敏度 :	95dB
Frequency Range	频响范围 :	63-5.4k Hz
Voice Coil Diameter	音圈直径 :	50mm/2 inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ135Ferrite Ring/H20mm

**MR08H83C-B**

Nominal Diameter	标准直径 :	210mm/8inch
Nominal Impedance	标称阻抗 :	16Ω
AES Power Handling	AES功率 :	150W (AES)
Maximum Power	最大功率 :	300W
Sensitivity 1W/1M	灵敏度 :	95dB
Frequency Range	频响范围 :	87-8k Hz
Voice Coil Diameter	音圈直径 :	50mm/2inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ135Ferrite Ring/H20mm

**MR08H48D-B**

Nominal Diameter	标准直径 :	210mm/8inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	350W (AES)
Maximum Power	最大功率 :	700W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	96-7k Hz
Voice Coil Diameter	音圈直径 :	75mm/3inch
Winding Material	线材 :	Aluminium
Magnet	磁体 :	Φ170Ferrite Ring/H25mm

**MR08MBX51-8**

Nominal Diameter	标准直径 :	208mm/8 inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	200W (AES)
Maximum Power	最大功率 :	400W
Sensitivity 1W/1M	灵敏度 :	96dB
Frequency Range	频响范围 :	62-4k Hz
Voice Coil Diameter	音圈直径 :	51mm/2 inch
Winding Material	线材 :	Aluminium
Magnet	磁体 :	Neodymium Ring

**MR08NDL65**

Nominal Diameter	标准直径 :	208mm/8inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	300W (AES)
Maximum Power	最大功率 :	600W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	70-4k Hz
Voice Coil Diameter	音圈直径 :	65mm/2.5inch
Winding Material	线材 :	Aluminium
Magnet	磁体 :	Neodymium Ring

**MR08N16D-B**

Nominal Diameter	标准直径 :	205mm/8inch
Nominal Impedance	标称阻抗 :	16Ω
AES Power Handling	AES功率 :	200W (AES)
Maximum Power	最大功率 :	400W
Sensitivity 1W/1M	灵敏度 :	98dB
Frequency Range	频响范围 :	88-7k Hz
Voice Coil Diameter	音圈直径 :	51mm/2inch
Winding Material	线材 :	Aluminium
Magnet	磁体 :	Neodymium Ring

**MR08N10D**

Nominal Diameter	标准直径 :	210mm/8inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	150W (AES)
Maximum Power	最大功率 :	300W
Sensitivity 1W/1M	灵敏度 :	95dB
Frequency Range	频响范围 :	63-5.2k Hz
Voice Coil Diameter	音圈直径 :	50mm/2 inch
Winding Material	线材 :	Aluminium
Magnet	磁体 :	Neodymium Ring

**MR08N29D**

Nominal Diameter	标准直径 :	210mm/8inch
Nominal Impedance	标称阻抗 :	16Ω
AES Power Handling	AES功率 :	200W (AES)
Maximum Power	最大功率 :	400W
Sensitivity 1W/1M	灵敏度 :	94dB
Frequency Range	频响范围 :	74-8k Hz
Voice Coil Diameter	音圈直径 :	50mm/2inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Neodymium Ring

**MR08H08**

Nominal Diameter	标准直径 :	210mm/8 inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	150W (AES)
Maximum Power	最大功率 :	300W
Sensitivity 1W/1M	灵敏度 :	98dB
Frequency Range	频响范围 :	62-71k Hz
Voice Coil Diameter	音圈直径 :	51mm/2 inch
Winding Material	线材 :	Copper-clad aluminum wire
Magnet	磁体 :	Neodymium Ring

**MR08N27D**

Nominal Diameter	标准直径 :	200mm/8inch
Nominal Impedance	标称阻抗 :	16Ω
AES Power Handling	AES功率 :	250W (AES)
Maximum Power	最大功率 :	500W
Sensitivity 1W/1M	灵敏度 :	96dB
Frequency Range	频响范围 :	76-6.5k Hz
Voice Coil Diameter	音圈直径 :	65mm/2.5 inch
Winding Material	线材 :	Aluminium
Magnet	磁体 :	Neodymium Ring

**MR08N36D**

Nominal Diameter	标准直径 :	210mm/8inch
Nominal Impedance	标称阻抗 :	16Ω
AES Power Handling	AES功率 :	250W (AES)
Maximum Power	最大功率 :	500W
Sensitivity 1W/1M	灵敏度 :	96dB
Frequency Range	频响范围 :	80-6k Hz
Voice Coil Diameter	音圈直径 :	65mm/2.5 inch
Winding Material	线材 :	Aluminium
Magnet	磁体 :	Neodymium Ring

**MR08N65-M**

Nominal Diameter	标准直径 :	200mm/8inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	250W (AES)
Maximum Power	最大功率 :	500W
Sensitivity 1W/1M	灵敏度 :	100dB
Frequency Range	频响范围 :	255-3k Hz
Voice Coil Diameter	音圈直径 :	65mm/2.5inch
Winding Material	线材 :	Aluminium
Magnet	磁体 :	Neodymium Ring

10"

PROFESSIONAL SPEAKER SERIES

**TS10H06A**

Nominal Diameter	标准直径 :	260mm/10inch
Nominal Impedance	标称阻抗 :	4Ω
AES Power Handling	AES功率 :	250W (AES)
Maximum Power	最大功率 :	500W
Sensitivity 1W/1M	灵敏度 :	93dB
Frequency Range	频响范围 :	75-5k Hz
Voice Coil Diameter	音圈直径 :	65mm/2.5inch
Winding Material	线 材 :	Copper
Magnet	磁 体 :	Φ156Ferrite Ring/H20mm

**TS10H08A**

Nominal Diameter	标准直径 :	260mm/10inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	300W (AES)
Maximum Power	最大功率 :	600W
Sensitivity 1W/1M	灵敏度 :	98dB
Frequency Range	频响范围 :	70-5k Hz
Voice Coil Diameter	音圈直径 :	75mm/3inch
Winding Material	线 材 :	Copper
Magnet	磁 体 :	Φ180Ferrite Ring/H20mm

**MR10H100**

Nominal Diameter	标准直径 :	260mm/10 inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	300W
Maximum Power	最大功率 :	600W
Sensitivity 1W/1M	灵敏度 :	96dB
Frequency Range	频响范围 :	70-3.5k Hz
Voice Coil Diameter	音圈直径 :	75mm/3 inch
Winding Material	线 材 :	Copper
Magnet	磁 体 :	Φ170Ferrite Ring/H20mm

**MR10H73D**

Nominal Diameter	标准直径 :	262mm/10inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	250W (AES)
Maximum Power	最大功率 :	500W
Sensitivity 1W/1M	灵敏度 :	96dB
Frequency Range	频响范围 :	56-6k Hz
Voice Coil Diameter	音圈直径 :	65mm/2.5inch
Winding Material	线 材 :	Copper
Magnet	磁 体 :	Φ170Ferrite Ring/H20mm

**MR10H100A**

Nominal Diameter	标准直径 :	262mm/10inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	300W (AES)
Maximum Power	最大功率 :	600W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	65-5.3k Hz
Voice Coil Diameter	音圈直径 :	75mm/3inch
Winding Material	线 材 :	Copper
Magnet	磁 体 :	Φ170Ferrite Ring/H20mm

**MR10H29D**

Nominal Diameter	标准直径 :	262mm/10inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	300W (AES)
Maximum Power	最大功率 :	600W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	80-5k Hz
Voice Coil Diameter	音圈直径 :	75mm/3inch
Winding Material	线 材 :	copper
Magnet	磁 体 :	Φ170Ferrite Ring/H20mm

**MR10H13D**

Nominal Diameter	标准直径 :	262mm/10inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	250W (AES)
Maximum Power	最大功率 :	500W
Sensitivity 1W/1M	灵敏度 :	96dB
Frequency Range	频响范围 :	60-4.6k Hz
Voice Coil Diameter	音圈直径 :	65mm/2.5inch
Winding Material	线 材 :	Copper
Magnet	磁 体 :	Φ156Ferrite Ring/H20mm

**MR10F50A-A**

Nominal Diameter	标准直径 :	260mm/10 inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	250W
Maximum Power	最大功率 :	500W
Sensitivity 1W/1M	灵敏度 :	95dB
Frequency Range	频响范围 :	65-4.1k Hz
Voice Coil Diameter	音圈直径 :	65mm/2.5 inch
Winding Material	线 材 :	Copper
Magnet	磁 体 :	Φ156Ferrite Ring/H20mm

**MR10H36E**

Nominal Diameter	标准直径 :	260mm/10inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	250W (AES)
Maximum Power	最大功率 :	500W
Sensitivity 1W/1M	灵敏度 :	96dB
Frequency Range	频响范围 :	65-4k Hz
Voice Coil Diameter	音圈直径 :	65mm/2.5inch
Winding Material	线 材 :	Copper
Magnet	磁 体 :	Φ156Ferrite Ring/H20mm

**MR10H60A**

Nominal Diameter	标准直径 :	260mm/10inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	250W (AES)
Maximum Power	最大功率 :	500W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	65-4.7k Hz
Voice Coil Diameter	音圈直径 :	65mm/2.5 inch
Winding Material	线 材 :	Copper
Magnet	磁 体 :	Φ156Ferrite Ring/H20mm

**MR10H61D**

Nominal Diameter	标准直径 :	260mm/10inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	250W (AES)
Maximum Power	最大功率 :	500W
Sensitivity 1W/1M	灵敏度 :	96dB
Frequency Range	频响范围 :	62-4k Hz
Voice Coil Diameter	音圈直径 :	65mm/2.5inch
Winding Material	线 材 :	Copper
Magnet	磁 体 :	Φ156Ferrite Ring/H20mm

**MR10H73C**

Nominal Diameter	标准直径 :	260mm/10inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	250W (AES)
Maximum Power	最大功率 :	500W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	58-4k Hz
Voice Coil Diameter	音圈直径 :	65mm/2.5inch
Winding Material	线 材 :	Copper
Magnet	磁 体 :	Φ156Ferrite Ring/H20mm

10"

PROFESSIONAL SPEAKER SERIES

**MR10H29**

Nominal Diameter	标准直径 :	260mm/10inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	250W (AES)
Maximum Power	最大功率 :	500W
Sensitivity 1W/1M	灵敏度 :	96dB
Frequency Range	频响范围 :	53-3.5k Hz
Voice Coil Diameter	音圈直径 :	65mm/2.5 inch
Winding Material	线 材 :	Copper
Magnet	磁 体 :	Φ156Ferrite Ring/H20mm

**MR10H40D**

Nominal Diameter	标准直径 :	260mm/10inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	250W (AES)
Maximum Power	最大功率 :	500W
Sensitivity 1W/1M	灵敏度 :	96dB
Frequency Range	频响范围 :	58-5k Hz
Voice Coil Diameter	音圈直径 :	65mm/2.5inch
Winding Material	线 材 :	Copper
Magnet	磁 体 :	Φ156Ferrite Ring/H20mm

**MR10H58D**

Nominal Diameter	标准直径 :	262mm/10 inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	300W (AES)
Maximum Power	最大功率 :	600W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	60-5.2k Hz
Voice Coil Diameter	音圈直径 :	65mm/2.5inch
Winding Material	线 材 :	COPPER
Magnet	磁 体 :	Φ156Ferrite Ring/H20mm

**MR10H65J**

Nominal Diameter	标准直径 :	266mm/10 inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	300W
Maximum Power	最大功率 :	600W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	57-3.8k Hz
Voice Coil Diameter	音圈直径 :	65mm/2.5 inch
Winding Material	线 材 :	Copper
Magnet	磁 体 :	Φ156Ferrite Ring/H20mm

**MR10H75J**

Nominal Diameter	标准直径 :	266mm/10 inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	350W
Maximum Power	最大功率 :	700W
Sensitivity 1W/1M	灵敏度 :	96dB
Frequency Range	频响范围 :	58~6k Hz
Voice Coil Diameter	音圈直径 :	75mm/3 inch
Winding Material	线 材 :	Aluminium
Magnet	磁 体 :	Φ170Ferrite Ring/H20mm

**MR10H36D**

Nominal Diameter	标准直径 :	261mm/10inch
Nominal Impedance	标称阻抗 :	16Ω
AES Power Handling	AES功率 :	300W (AES)
Maximum Power	最大功率 :	600W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	60-4.5k Hz
Voice Coil Diameter	音圈直径 :	75mm/3 inch
Winding Material	线 材 :	Aluminium
Magnet	磁 体 :	Φ170Ferrite Ring/H20mm

**MR10H90**

Nominal Diameter	标准直径 :	261mm/10inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	300W (AES)
Maximum Power	最大功率 :	600W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	65-4.4k Hz
Voice Coil Diameter	音圈直径 :	75mm/3 inch
Winding Material	线 材 :	Aluminium
Magnet	磁 体 :	Φ170Ferrite Ring/H20mm

**MR10H38D-A**

Nominal Diameter	标准直径 :	262mm/10 inch
Nominal Impedance	标称阻抗 :	16Ω
AES Power Handling	AES功率 :	300W (AES)
Maximum Power	最大功率 :	600W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	78-5k Hz
Voice Coil Diameter	音圈直径 :	75mm/3inch
Winding Material	线 材 :	Aluminium
Magnet	磁 体 :	Φ180Ferrite Ring/H20mm

**MR10H26E**

Nominal Diameter	标准直径 :	262mm/10inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	300W (AES)
Maximum Power	最大功率 :	600W
Sensitivity 1W/1M	灵敏度 :	96dB
Frequency Range	频响范围 :	56-6k Hz
Voice Coil Diameter	音圈直径 :	75mm/3inch
Winding Material	线 材 :	Copper
Magnet	磁 体 :	Φ170Ferrite Ring/H20mm

**MR10MD26**

Nominal Diameter	标准直径 :	262mm/10 inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	300W
Maximum Power	最大功率 :	600W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	60~4.5k Hz
Voice Coil Diameter	音圈直径 :	75mm/3 inch
Winding Material	线 材 :	Aluminium
Magnet	磁 体 :	Φ180Ferrite Ring/H20mm

**MR10H99C**

Nominal Diameter	标准直径 :	260mm/10 inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	300W
Maximum Power	最大功率 :	600W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	61-4k Hz
Voice Coil Diameter	音圈直径 :	75mm/3 inch
Winding Material	线 材 :	Copper
Magnet	磁 体 :	Φ190Ferrite Ring/H20mm

**MR10H95C**

Nominal Diameter	标准直径 :	262mm/10inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	400W (AES)
Maximum Power	最大功率 :	800W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	53-4.3k Hz
Voice Coil Diameter	音圈直径 :	86mm/3.5 inch
Winding Material	线 材 :	Aluminium
Magnet	磁 体 :	Φ190Ferrite Ring/H25mm

10"

PROFESSIONAL
SPEAKER SERIES



MR10N70D-A

Nominal Diameter	标准直径 :	260mm/10inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	350W (AES)
Maximum Power	最大功率 :	700W
Sensitivity 1W/1M	灵敏度 :	98dB
Frequency Range	频响范围 :	70-6k Hz
Voice Coil Diameter	音圈直径 :	75mm/3inch
Winding Material	线材 :	Aluminium
Magnet	磁体 :	Neodymium Ring



MR10NW65-8

Nominal Diameter	标准直径 :	260mm/10 inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	300W
Maximum Power	最大功率 :	600W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	65-6k Hz
Voice Coil Diameter	音圈直径 :	65mm/2.5 inch
Winding Material	线材 :	Aluminium
Magnet	磁体 :	Neodymium Ring



MR10NW65-16

Nominal Diameter	标准直径 :	260mm/10inch
Nominal Impedance	标称阻抗 :	16Ω
AES Power Handling	AES功率 :	300W (AES)
Maximum Power	最大功率 :	600W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	65-6k Hz
Voice Coil Diameter	音圈直径 :	65mm/2.5inch
Winding Material	线材 :	Aluminium
Magnet	磁体 :	Neodymium Ring



TS10N09A

Nominal Diameter	标准直径 :	260mm/10inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	300W (AES)
Maximum Power	最大功率 :	600W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	65-6.5k Hz
Voice Coil Diameter	音圈直径 :	65mm/2.5inch
Winding Material	线材 :	Aluminium
Magnet	磁体 :	Neodymium Ring



MR10N65M-8

Nominal Diameter	标准直径 :	260mm/10inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	300W (AES)
Maximum Power	最大功率 :	600W
Sensitivity 1W/1M	灵敏度 :	99dB
Frequency Range	频响范围 :	82-8k Hz
Voice Coil Diameter	音圈直径 :	65mm/2.5inch
Winding Material	线材 :	Aluminium
Magnet	磁体 :	Neodymium Ring



MR10N10D

Nominal Diameter	标准直径 :	260mm/10inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	300W (AES)
Maximum Power	最大功率 :	600W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	65-6.0k Hz
Voice Coil Diameter	音圈直径 :	65mm/2.5inch
Winding Material	线材 :	Aluminium
Magnet	磁体 :	Neodymium Ring



MR10N01E-A

Nominal Diameter	标准直径 :	260mm/10inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	250W (AES)
Maximum Power	最大功率 :	500W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	70-5k Hz
Voice Coil Diameter	音圈直径 :	65mm/2.5inch
Winding Material	线材 :	Aluminium
Magnet	磁体 :	Neodymium Ring



MR10N02E-B

Nominal Diameter	标准直径 :	260mm/10inch
Nominal Impedance	标称阻抗 :	16Ω
AES Power Handling	AES功率 :	300W (AES)
Maximum Power	最大功率 :	600W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	74-4k Hz
Voice Coil Diameter	音圈直径 :	75mm/3inch
Winding Material	线材 :	Aluminium
Magnet	磁体 :	Neodymium Ring



MA10ND18-A

Nominal Diameter	标准直径 :	262mm/10inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	300W (AES)
Maximum Power	最大功率 :	600W
Sensitivity 1W/1M	灵敏度 :	96dB
Frequency Range	频响范围 :	46-2.5k Hz
Voice Coil Diameter	音圈直径 :	75mm/3inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Neodymium Ring



MR10N32D

Nominal Diameter	标准直径 :	261mm/10inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	300W (AES)
Maximum Power	最大功率 :	600W
Sensitivity 1W/1M	灵敏度 :	96dB
Frequency Range	频响范围 :	66-5.0k Hz
Voice Coil Diameter	音圈直径 :	75mm/3inch
Winding Material	线材 :	Aluminium
Magnet	磁体 :	Neodymium Ring



MR10N90D

Nominal Diameter	标准直径 :	260mm/10inch
Nominal Impedance	标称阻抗 :	16Ω
AES Power Handling	AES功率 :	350W (AES)
Maximum Power	最大功率 :	700W
Sensitivity 1W/1M	灵敏度 :	98dB
Frequency Range	频响范围 :	55-3k Hz
Voice Coil Diameter	音圈直径 :	75mm/3inch
Winding Material	线材 :	Aluminium
Magnet	磁体 :	Neodymium Ring



MR10N75-M

Nominal Diameter	标准直径 :	260mm/10inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	350W (AES)
Maximum Power	最大功率 :	700W
Sensitivity 1W/1M	灵敏度 :	101dB
Frequency Range	频响范围 :	225-4k Hz
Voice Coil Diameter	音圈直径 :	75mm/3inch
Winding Material	线材 :	Aluminium
Magnet	磁体 :	Neodymium Ring

**MR12H100**

Nominal Diameter	标准直径:	312mm/12inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	300W (AES)
Maximum Power	最大功率:	600W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	55-4k Hz
Voice Coil Diameter	音圈直径:	75mm/3 inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ170Ferrite Ring/H20mm

**MR12H98D**

Nominal Diameter	标准直径:	312mm/12inch
Nominal Impedance	标称阻抗:	16Ω
AES Power Handling	AES功率:	300W (AES)
Maximum Power	最大功率:	600W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	56-5k Hz
Voice Coil Diameter	音圈直径:	75mm/3 inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Φ180Ferrite Ring/H20mm

**EL12-75C**

Nominal Diameter	标准直径:	312mm/12 inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	300W
Maximum Power	最大功率:	600W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	59-5k Hz
Voice Coil Diameter	音圈直径:	75mm/3 inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ170Ferrite Ring/H20mm

**EL12-19**

Nominal Diameter	标准直径:	312mm/12 inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	300W
Maximum Power	最大功率:	600W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	57-4.7k Hz
Voice Coil Diameter	音圈直径:	75mm/3 inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ190Ferrite Ring/H20mm

**MR12H100A**

Nominal Diameter	标准直径:	320mm/12inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	400W (AES)
Maximum Power	最大功率:	800W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	64-3.9k Hz
Voice Coil Diameter	音圈直径:	75mm/3 inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Φ190Ferrite Ring/H25mm

**MA12H15G**

Nominal Diameter	标准直径:	320m/12inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	400W (AES)
Maximum Power	最大功率:	800W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	66-3.1k Hz
Voice Coil Diameter	音圈直径:	75mm/3 inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ190Ferrite Ring/H20mm

**MR12H86E**

Nominal Diameter	标准直径:	315mm/12inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	400W (AES)
Maximum Power	最大功率:	800W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	55-4.5k Hz
Voice Coil Diameter	音圈直径:	86mm/3.5inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Φ190Ferrite Ring/H20mm

**TS12H19C**

Nominal Diameter	标准直径:	315mm/12inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	350W (AES)
Maximum Power	最大功率:	700W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	58-5k Hz
Voice Coil Diameter	音圈直径:	75mm/3inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ190Ferrite Ring/H20mm

**TS12H01A**

Nominal Diameter	标准直径:	315mm/12inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	400W (AES)
Maximum Power	最大功率:	800W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	53-4k Hz
Voice Coil Diameter	音圈直径:	86mm/3.5inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ190Ferrite Ring/H25mm

**TS12H08A**

Nominal Diameter	标准直径:	315mm/12inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	350W (AES)
Maximum Power	最大功率:	700W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	60-5k Hz
Voice Coil Diameter	音圈直径:	75mm/3inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Φ190Ferrite Ring/H20mm

**MR12H39E**

Nominal Diameter	标准直径:	315mm/12inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	350W (AES)
Maximum Power	最大功率:	700W
Sensitivity 1W/1M	灵敏度:	96.5 dB
Frequency Range	频响范围:	54-4k Hz
Voice Coil Diameter	音圈直径:	75mm/3inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ190Ferrite Ring/H20mm

**BH12H01**

Nominal Diameter	标准直径:	315mm/12inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	350W (AES)
Maximum Power	最大功率:	700W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	55-5k Hz
Voice Coil Diameter	音圈直径:	75mm/3inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ190Ferrite Ring/H20mm

**MR12H23E-16**

Nominal Diameter	标准直径 :	315mm/12inch
Nominal Impedance	标称阻抗 :	16Ω
AES Power Handling	AES功率 :	200W (AES)
Maximum Power	最大功率 :	400W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	95-18k Hz
Voice Coil Diameter	音圈直径 :	50mm/2inch
Winding Material	线材 :	Aluminium
Magnet	磁体 :	Φ170Ferrite Ring/H20mm

**MR12H17G**

Nominal Diameter	标准直径 :	315mm / 12inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	350W (AES)
Maximum Power	最大功率 :	700W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	63-5k Hz
Voice Coil Diameter	音圈直径 :	75mm / 3inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ190Ferrite Ring/H20mm

**MR12H16E**

Nominal Diameter	标准直径 :	315mm/12inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	450W (AES)
Maximum Power	最大功率 :	900W
Sensitivity 1W/1M	灵敏度 :	99dB
Frequency Range	频响范围 :	58-3k Hz
Voice Coil Diameter	音圈直径 :	75mm/3 inch
Winding Material	线材 :	Aluminium
Magnet	磁体 :	Φ190Ferrite Ring/H25mm

**MR12H10G**

Nominal Diameter	标准直径 :	315mm/12inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	350W (AES)
Maximum Power	最大功率 :	700W
Sensitivity 1W/1M	灵敏度 :	99dB
Frequency Range	频响范围 :	82-5.5k HZ
Voice Coil Diameter	音圈直径 :	75mm/3inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ190Ferrite Ring/H25mm

**MR12H16E-A**

Nominal Diameter	标准直径 :	315mm/12inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	500W (AES)
Maximum Power	最大功率 :	1000W
Sensitivity 1W/1M	灵敏度 :	99dB
Frequency Range	频响范围 :	58-3k Hz
Voice Coil Diameter	音圈直径 :	75mm/3inch
Winding Material	线材 :	Aluminium
Magnet	磁体 :	Φ200Ferrite Ring/H25mm

**MR12H73C**

Nominal Diameter	标准直径 :	315mm/12inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	300W (AES)
Maximum Power	最大功率 :	600W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	60-4.5k Hz
Voice Coil Diameter	音圈直径 :	65mm/2.5 inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ170Ferrite Ring/H20mm

**MR12H90**

Nominal Diameter	标准直径 :	315m/12inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	400W (AES)
Maximum Power	最大功率 :	800W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	56-5.8k Hz
Voice Coil Diameter	音圈直径 :	75mm/3 inch
Winding Material	线材 :	Aluminium
Magnet	磁体 :	Φ190Ferrite Ring/H20mm

**MR12H95D-C**

Nominal Diameter	标准直径 :	315mm/12inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	400W (AES)
Maximum Power	最大功率 :	800W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	54-5k Hz
Voice Coil Diameter	音圈直径 :	75mm/3inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ190Ferrite Ring/H20mm

**MR12H61D**

Nominal Diameter	标准直径 :	315mm/12inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	300W (AES)
Maximum Power	最大功率 :	600W
Sensitivity 1W/1M	灵敏度 :	96dB
Frequency Range	频响范围 :	70-5k Hz
Voice Coil Diameter	音圈直径 :	75mm/3 inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ190Ferrite Ring/H20mm

**MR12H36E**

Nominal Diameter	标准直径 :	315mm/12inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	350W (AES)
Maximum Power	最大功率 :	700W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	63-5k Hz
Voice Coil Diameter	音圈直径 :	75mm/3inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ190Ferrite Ring/H20mm

**MR12H60A**

Nominal Diameter	标准直径 :	315mm/12inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	350W (AES)
Maximum Power	最大功率 :	700W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	60-4.4k Hz
Voice Coil Diameter	音圈直径 :	75mm/3 inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ190Ferrite Ring/H20mm

**MR12H55E**

Nominal Diameter	标准直径 :	315mm/12inch
Nominal Impedance	标称阻抗 :	16Ω
AES Power Handling	AES功率 :	350W (AES)
Maximum Power	最大功率 :	700W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	54-4.5k Hz
Voice Coil Diameter	音圈直径 :	75mm/3inch
Winding Material	线材 :	Aluminium
Magnet	磁体 :	Φ190Ferrite Ring/H20mm

**MR12H15D-3**

Nominal Diameter	标准直径 :	315mm/12inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	300W (AES)
Maximum Power	最大功率 :	600W
Sensitivity 1W/1M	灵敏度 :	96dB
Frequency Range	频响范围 :	65-5.8k Hz
Voice Coil Diameter	音圈直径 :	75mm/3inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ190Ferrite Ring/H20mm

**MR12H18E**

Nominal Diameter	标准直径 :	315mm/12inch
Nominal Impedance	标称阻抗 :	4Ω
AES Power Handling	AES功率 :	350W (AES)
Maximum Power	最大功率 :	700W
Sensitivity 1W/1M	灵敏度 :	95dB
Frequency Range	频响范围 :	42-2k Hz
Voice Coil Diameter	音圈直径 :	75mm/3inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ190Ferrite Ring/H20mm

**MR12H07D**

Nominal Diameter	标准直径 :	314mm/12inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	400W (AES)
Maximum Power	最大功率 :	800W
Sensitivity 1W/1M	灵敏度 :	95dB
Frequency Range	频响范围 :	39-5.6k Hz
Voice Coil Diameter	音圈直径 :	75mm/3 inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ190Ferrite Ring/H20mm

**MR12H30**

Nominal Diameter	标准直径 :	314mm/12inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	400W (AES)
Maximum Power	最大功率 :	800W
Sensitivity 1W/1M	灵敏度 :	95dB
Frequency Range	频响范围 :	40-3k HZ
Voice Coil Diameter	音圈直径 :	75mm/3 inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ190Ferrite Ring/H20mm

**MR12H06E**

Nominal Diameter	标准直径 :	315mm/12inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	400W (AES)
Maximum Power	最大功率 :	800W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	47-3k Hz
Voice Coil Diameter	音圈直径 :	75mm/3 inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ190*2Ferrite Ring/H20*2mm

**MR12TBX100**

Nominal Diameter	标准直径 :	315mm/12 inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	600W (AES)
Maximum Power	最大功率 :	1200W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	58-2.7k Hz
Voice Coil Diameter	音圈直径 :	100mm/4 inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ220Ferrite Ring/H25mm

**MR12H08**

Nominal Diameter	标准直径 :	320mm/12 inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	400W
Maximum Power	最大功率 :	800W
Sensitivity 1W/1M	灵敏度 :	96dB
Frequency Range	频响范围 :	68~3.7k Hz
Voice Coil Diameter	音圈直径 :	75mm/3 inch
Winding Material	线材 :	Aluminium
Magnet	磁体 :	Φ180Ferrite Ring/H20mm

**MR12H351**

Nominal Diameter	标准直径 :	320mm/12 inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	400W
Maximum Power	最大功率 :	800W
Sensitivity 1W/1M	灵敏度 :	96dB
Frequency Range	频响范围 :	58~3.3k Hz
Voice Coil Diameter	音圈直径 :	86mm/3.5 inch
Winding Material	线材 :	Aluminium
Magnet	磁体 :	Φ190Ferrite Ring/H25mm

**MR12H49D**

Nominal Diameter	标准直径 :	320mm/12 inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	350W
Maximum Power	最大功率 :	700W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	54-5.6k Hz
Voice Coil Diameter	音圈直径 :	75mm/3 inch
Winding Material	线材 :	Aluminium
Magnet	磁体 :	Φ190Ferrite Ring/H20mm

**MR12H65J-A**

Nominal Diameter	标准直径 :	322mm/12inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	300W (AES)
Maximum Power	最大功率 :	600W
Sensitivity 1W/1M	灵敏度 :	96dB
Frequency Range	频响范围 :	60-5.5k Hz
Voice Coil Diameter	音圈直径 :	65mm/2.5inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ170Ferrite Ring/H20mm

**MR12H75D**

Nominal Diameter	标准直径 :	322mm/12inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	400W (AES)
Maximum Power	最大功率 :	800W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	55-5.2k Hz
Voice Coil Diameter	音圈直径 :	75mm/3 inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ190Ferrite Ring/H20mm

**MR12H052**

Nominal Diameter	标准直径 :	322mm/12inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	400W (AES)
Maximum Power	最大功率 :	800W
Sensitivity 1W/1M	灵敏度 :	98dB
Frequency Range	频响范围 :	53-5k Hz
Voice Coil Diameter	音圈直径 :	75mm/3inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ190Ferrite Ring/H20mm

**MR12H96C**

Nominal Diameter	标准直径 :	319mm/12inch
Nominal Impedance	标称阻抗 :	4Ω
AES Power Handling	AES功率 :	300W (AES)
Maximum Power	最大功率 :	600W
Sensitivity 1W/1M	灵敏度 :	94dB
Frequency Range	频响范围 :	28-2.7k Hz
Voice Coil Diameter	音圈直径 :	65mm/2.5 inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ156Ferrite Ring/H25mm

**MR12H96D**

Nominal Diameter	标准直径 :	319mm/12inch
Nominal Impedance	标称阻抗 :	4Ω
AES Power Handling	AES功率 :	400W
Maximum Power	最大功率 :	800W
Sensitivity 1W/1M	灵敏度 :	95dB
Frequency Range	频响范围 :	35-2.7k Hz
Voice Coil Diameter	音圈直径 :	75mm/3 inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ170Ferrite Ring/H25mm

**MR12H26E**

Nominal Diameter	标准直径 :	315mm/12 inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	300W (AES)
Maximum Power	最大功率 :	600W
Sensitivity 1W/1M	灵敏度 :	96dB
Frequency Range	频响范围 :	54-5k Hz
Voice Coil Diameter	音圈直径 :	75mm/3 inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ190Ferrite Ring/H20mm

**MR12F75D**

Nominal Diameter	标准直径 :	309mm/12inch
Nominal Impedance	标称阻抗 :	16Ω
AES Power Handling	AES功率 :	120W (AES)
Maximum Power	最大功率 :	240W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	136-17k Hz
Voice Coil Diameter	音圈直径 :	38mm/1.5 inch
Winding Material	线材 :	Aluminium
Magnet	磁体 :	Φ156Ferrite Ring/H20mm

**MR12H100D**

Nominal Diameter	标准直径 :	317mm/12inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	300W (AES)
Maximum Power	最大功率 :	600W
Sensitivity 1W/1M	灵敏度 :	96dB
Frequency Range	频响范围 :	50-4.5k Hz
Voice Coil Diameter	音圈直径 :	75mm/3 inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ190Ferrite Ring/H20mm

**MR12PLB76-8**

Nominal Diameter	标准直径 :	315mm /12 inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	350W (AES)
Maximum Power	最大功率 :	700W
Sensitivity 1W/1M	灵敏度 :	98dB
Frequency Range	频响范围 :	50-3k Hz
Voice Coil Diameter	音圈直径 :	75mm /3 inch
Winding Material	线材 :	Aluminium
Magnet	磁体 :	Φ180Ferrite Ring/H20mm

Fiber

**MR12H97D**

Nominal Diameter	标准直径 :	316mm/12inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	500W (AES)
Maximum Power	最大功率 :	1000W
Sensitivity 1W/1M	灵敏度 :	96dB
Frequency Range	频响范围 :	45-3.2k Hz
Voice Coil Diameter	音圈直径 :	100mm/4 inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ220Ferrite Ring/H25mm

**MR12H35D**

Nominal Diameter	标准直径 :	316mm/12inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	500W (AES)
Maximum Power	最大功率 :	1000W
Sensitivity 1W/1M	灵敏度 :	96dB
Frequency Range	频响范围 :	47-3.2k Hz
Voice Coil Diameter	音圈直径 :	100mm/4 inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ220Ferrite Ring/H20mm

**MR12H200**

Nominal Diameter	标准直径 :	315mm/12 inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	600W (AES)
Maximum Power	最大功率 :	1200W
Sensitivity 1W/1M	灵敏度 :	96dB
Frequency Range	频响范围 :	61-3k Hz
Voice Coil Diameter	音圈直径 :	100mm/4inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ200*2Ferrite Ring/H20*2mm

**MR12H70**

Nominal Diameter	标准直径 :	315mm /12 inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	500W
Maximum Power	最大功率 :	1000W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	67-2.9k Hz
Voice Coil Diameter	音圈直径 :	100mm/4inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ220Ferrite Ring/H25mm

**MR12H16G**

Nominal Diameter	标准直径 :	315mm /12 inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	500W
Maximum Power	最大功率 :	1000W
Sensitivity 1W/1M	灵敏度 :	96dB
Frequency Range	频响范围 :	50~3.2k Hz
Voice Coil Diameter	音圈直径 :	100mm/4 inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ220Ferrite Ring/H20mm

**MR12H01FT**

Nominal Diameter	标准直径 :	315mm/12inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	550W (AES)
Maximum Power	最大功率 :	1100W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	60-5k Hz
Voice Coil Diameter	音圈直径 :	100mm/4inch
Winding Material	线材 :	Aluminium
Magnet	磁体 :	Φ220Ferrite Ring/H25mm

**DF12H01A**

Nominal Diameter	标准直径 :	320mm/12 inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	800W
Maximum Power	最大功率 :	1600W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	48~4k Hz
Voice Coil Diameter	音圈直径 :	100mm/4 inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ220Ferrite Ring/H25mm

**DF12H02A**

Nominal Diameter	标准直径 :	320mm/12 inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	1200W
Maximum Power	最大功率 :	2400W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	40~2.5k Hz
Voice Coil Diameter	音圈直径 :	115mm/4.5 inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ253Ferrite Ring/H25mm

**MR12H63E**

Nominal Diameter	标准直径 :	315mm/12inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	700W (AES)
Maximum Power	最大功率 :	1400W
Sensitivity 1W/1M	灵敏度 :	93dB
Frequency Range	频响范围 :	65~2k Hz
Voice Coil Diameter	音圈直径 :	115mm/4.5inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ253*2Ferrite Ring/H25*2mm

**MR12H28E**

Nominal Diameter	标准直径 :	315mm/12inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	500W (AES)
Maximum Power	最大功率 :	1000W
Sensitivity 1W/1M	灵敏度 :	96dB
Frequency Range	频响范围 :	55~4k Hz
Voice Coil Diameter	音圈直径 :	100mm/4inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ220Ferrite Ring/H20mm

**MR12H03E**

Nominal Diameter	标准直径 :	315mm/12inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	700W (AES)
Maximum Power	最大功率 :	1400W
Sensitivity 1W/1M	灵敏度 :	94dB
Frequency Range	频响范围 :	85HZ~2k Hz
Voice Coil Diameter	音圈直径 :	115mm/4.5 inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ220*2Ferrite Ring/H25*2mm

**MR12H05E-B**

Nominal Diameter	标准直径 :	315mm/12inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	600W (AES)
Maximum Power	最大功率 :	1200W
Sensitivity 1W/1M	灵敏度 :	96dB
Frequency Range	频响范围 :	52~2.6k Hz
Voice Coil Diameter	音圈直径 :	100mm/4inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ220*2Ferrite Ring/H20*2mm

**MR12H76E**

Nominal Diameter	标准直径 :	315mm/12inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	800W (AES)
Maximum Power	最大功率 :	1600W
Sensitivity 1W/1M	灵敏度 :	93dB
Frequency Range	频响范围 :	92~2.5k Hz
Voice Coil Diameter	音圈直径 :	125mm/5inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ253*2Ferrite Ring/H25*2mm

**MR12H51D**

Nominal Diameter	标准直径 :	315mm/12inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	1200W (AES)
Maximum Power	最大功率 :	2400W
Sensitivity 1W/1M	灵敏度 :	96dB
Frequency Range	频响范围 :	71~2k Hz
Voice Coil Diameter	音圈直径 :	125mm/5inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ253*4Ferrite Ring/H20*4mm

**MR12N10D**

Nominal Diameter	标准直径 :	316mm/12inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	350W (AES)
Maximum Power	最大功率 :	700W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	54~5.0k Hz
Voice Coil Diameter	音圈直径 :	75mm/3inch
Winding Material	线材 :	Aluminium
Magnet	磁体 :	Neodymium Ring

**MR12N75UL**

Nominal Diameter	标准直径 :	315mm/12inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	350W (AES)
Maximum Power	最大功率 :	700W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	60~5k Hz
Voice Coil Diameter	音圈直径 :	75mm/3inch
Winding Material	线材 :	Aluminium
Magnet	磁体 :	Neodymium Ring

**MR12NW76-8**

Nominal Diameter	标准直径 :	315mm/12inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	450W (AES)
Maximum Power	最大功率 :	900W
Sensitivity 1W/1M	灵敏度 :	98dB
Frequency Range	频响范围 :	52~4k Hz
Voice Coil Diameter	音圈直径 :	75mm/3inch
Winding Material	线材 :	Aluminium
Magnet	磁体 :	Neodymium Ring

**MR12N16E-8**

Nominal Diameter	标准直径 :	315mm/12inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	450W (AES)
Maximum Power	最大功率 :	900W
Sensitivity 1W/1M	灵敏度 :	98dB
Frequency Range	频响范围 :	52~4k Hz
Voice Coil Diameter	音圈直径 :	75mm/3inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Neodymium Ring

**MR12N01E-A**

Nominal Diameter	标准直径 :	315mm/12inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	350W (AES)
Maximum Power	最大功率 :	700W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	65-4k Hz
Voice Coil Diameter	音圈直径 :	75mm/3inch
Winding Material	线材 :	Aluminium
Magnet	磁体 :	Neodymium Ring

**MR12N16E-A**

Nominal Diameter	标准直径 :	315mm/12inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	400W (AES)
Maximum Power	最大功率 :	800W
Sensitivity 1W/1M	灵敏度 :	98dB
Frequency Range	频响范围 :	62-5k Hz
Voice Coil Diameter	音圈直径 :	75mm/3inch
Winding Material	线材 :	Aluminium
Magnet	磁体 :	Neodymium Ring

**MR12N16E-16**

Nominal Diameter	标准直径 :	315mm/12inch
Nominal Impedance	标称阻抗 :	16Ω
AES Power Handling	AES功率 :	450W (AES)
Maximum Power	最大功率 :	900W
Sensitivity 1W/1M	灵敏度 :	98dB
Frequency Range	频响范围 :	50-4.5k Hz
Voice Coil Diameter	音圈直径 :	75mm/3inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Neodymium Ring

**MR12NDL88A**

Nominal Diameter	标准直径 :	315mm / 12inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	450W (AES)
Maximum Power	最大功率 :	900W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	55-3.8k Hz
Voice Coil Diameter	音圈直径 :	86mm /3.5inch
Winding Material	线材 :	Aluminium
Magnet	磁体 :	Neodymium Ring

**MR12NBX100**

Nominal Diameter	标准直径 :	315mm/12inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	800W (AES)
Maximum Power	最大功率 :	1600W
Sensitivity 1W/1M	灵敏度 :	96dB
Frequency Range	频响范围 :	45-2k Hz
Voice Coil Diameter	音圈直径 :	100mm/4inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Neodymium Ring

**MR12N2226**

Nominal Diameter	标准直径 :	310mm / inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	350W (AES)
Maximum Power	最大功率 :	700W
Sensitivity 1W/1M	灵敏度 :	98dB
Frequency Range	频响范围 :	67-4.2k Hz
Voice Coil Diameter	音圈直径 :	75mm /3inch
Winding Material	线材 :	Aluminium
Magnet	磁体 :	Neodymium Ring

**TS12N09A**

Nominal Diameter	标准直径 :	315mm/12inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	400W (AES)
Maximum Power	最大功率 :	800W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	54-5k Hz
Voice Coil Diameter	音圈直径 :	75mm/3inch
Winding Material	线材 :	Aluminium
Magnet	磁体 :	Neodymium Ring

**MR12N90D-B**

Nominal Diameter	标准直径 :	312mm/12inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	350W (AES)
Maximum Power	最大功率 :	700W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	54-5.5k Hz
Voice Coil Diameter	音圈直径 :	75mm/3inch
Winding Material	线材 :	Aluminium
Magnet	磁体 :	Neodymium Ring

**MR12N30E**

Nominal Diameter	标准直径 :	312mm/12inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	400W (AES)
Maximum Power	最大功率 :	800W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	58-5.5k Hz
Voice Coil Diameter	音圈直径 :	75mm/3 inch
Winding Material	线材 :	Aluminium
Magnet	磁体 :	Neodymium Ring

**MR12N02FT**

Nominal Diameter	标准直径 :	315mm/12inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	400W (AES)
Maximum Power	最大功率 :	800W
Sensitivity 1W/1M	灵敏度 :	98dB
Frequency Range	频响范围 :	57-5k Hz
Voice Coil Diameter	音圈直径 :	75mm/3inch
Winding Material	线材 :	Aluminium
Magnet	磁体 :	Neodymium Ring

**MR12X351**

Nominal Diameter	标准直径 :	300mm/12 inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	400W
Maximum Power	最大功率 :	800W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	51-3.7k Hz
Voice Coil Diameter	音圈直径 :	86mm/3.5 inch
Winding Material	线材 :	Aluminium
Magnet	磁体 :	Neodymium Ring

**MR12N100J**

Nominal Diameter	标准直径 :	312mm/12 inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	600W
Maximum Power	最大功率 :	1200W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	47-2.8k Hz
Voice Coil Diameter	音圈直径 :	100mm/4inch
Winding Material	线材 :	Aluminium
Magnet	磁体 :	Neodymium Ring

**MR15H27D**

Nominal Diameter	标准直径:	400mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	400W (AES)
Maximum Power	最大功率:	800W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	45-3k Hz
Voice Coil Diameter	音圈直径:	75mm/3 inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ190Ferrite Ring/H20mm

**MR15H16D**

Nominal Diameter	标准直径:	400mm/15 inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	600W (AES)
Maximum Power	最大功率:	1200W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	52-3.8k Hz
Voice Coil Diameter	音圈直径:	100mm/4 inch
Winding Material	线材:	copper
Magnet	磁体:	Φ220Ferrite Ring/H25mm

**MR15H100A**

Nominal Diameter	标准直径:	400mm/15 inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	600W (AES)
Maximum Power	最大功率:	1200W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	42-3.5k Hz
Voice Coil Diameter	音圈直径:	100mm/4 inch
Winding Material	线材:	copper
Magnet	磁体:	Φ220Ferrite Ring/H25mm

**MR15H39E**

Nominal Diameter	标准直径:	395mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	400W (AES)
Maximum Power	最大功率:	800W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	50-4k Hz
Voice Coil Diameter	音圈直径:	75mm/3inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ190Ferrite Ring/H20mm

**MR15H86E**

Nominal Diameter	标准直径:	395mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	450W (AES)
Maximum Power	最大功率:	900W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	50-2.5k Hz
Voice Coil Diameter	音圈直径:	86mm/3.5inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ190Ferrite Ring/H20mm

**MA15H15G**

Nominal Diameter	标准直径:	400mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	600W (AES)
Maximum Power	最大功率:	1200W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	35-2.5k Hz
Voice Coil Diameter	音圈直径:	100mm/4 inch
Winding Material	线材:	copper
Magnet	磁体:	Φ220Ferrite Ring/H25mm

**TS15H12E**

Nominal Diameter	标准直径:	395mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	400W (AES)
Maximum Power	最大功率:	800W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	44-3.5k Hz
Voice Coil Diameter	音圈直径:	75mm/3inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ190Ferrite Ring/H20mm

**TS15H15E**

Nominal Diameter	标准直径:	395mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	500W (AES)
Maximum Power	最大功率:	1000W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	42-3.5k Hz
Voice Coil Diameter	音圈直径:	100mm/4inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ220Ferrite Ring/H25mm

**TS15H220C**

Nominal Diameter	标准直径:	395mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	600W (AES)
Maximum Power	最大功率:	1200W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	46-3.5k Hz
Voice Coil Diameter	音圈直径:	100mm/4inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ220Ferrite Ring/H25mm

**TS15H13E**

Nominal Diameter	标准直径:	395mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	800W (AES)
Maximum Power	最大功率:	1600W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	51-3k Hz
Voice Coil Diameter	音圈直径:	115mm/4.5inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ253Ferrite Ring/H25mm

**BH15H03**

Nominal Diameter	标准直径:	395mm / 15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	550W (AES)
Maximum Power	最大功率:	1100W
Sensitivity 1W/1M	灵敏度:	98dB
Frequency Range	频响范围:	50-4.5k Hz
Voice Coil Diameter	音圈直径:	100mm / 4inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ220Ferrite Ring/H25mm

**BH15H01**

Nominal Diameter	标准直径:	395mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	400W (AES)
Maximum Power	最大功率:	800W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	45-4k Hz
Voice Coil Diameter	音圈直径:	75mm/3inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Φ190Ferrite Ring/H25mm

**BH15H02**

Nominal Diameter	标准直径:	395mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	450W (AES)
Maximum Power	最大功率:	900W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	43-3k Hz
Voice Coil Diameter	音圈直径:	86mm/3.5 inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Φ200Ferrite Ring/H20mm

**BH15H07**

Nominal Diameter	标准直径:	395mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	1100W (AES)
Maximum Power	最大功率:	2200W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	40-3k Hz
Voice Coil Diameter	音圈直径:	115mm/4.5inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Φ253Ferrite Ring/H25mm

**BH15H06**

Nominal Diameter	标准直径:	395mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	1300W (AES)
Maximum Power	最大功率:	2600W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	38-2k Hz
Voice Coil Diameter	音圈直径:	125mm/5inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ280Ferrite Ring/H25mm

**EL15-19**

Nominal Diameter	标准直径:	394mm/15 inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	350W (AES)
Maximum Power	最大功率:	700W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	48-3k Hz
Voice Coil Diameter	音圈直径:	75mm/3 inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ190Ferrite Ring/H20mm

**EL15900**

Nominal Diameter	标准直径:	394mm/15 inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	500W (AES)
Maximum Power	最大功率:	1000W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	51-2.6k Hz
Voice Coil Diameter	音圈直径:	100mm/4 inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ220Ferrite Ring/H25mm

**MR15H200**

Nominal Diameter	标准直径:	380mm/15 inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	700W
Maximum Power	最大功率:	1400W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	53-2.2k Hz
Voice Coil Diameter	音圈直径:	100mm/4 inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ220*2Ferrite Ring/H20*2mm

**JY15H03**

Nominal Diameter	标准直径:	395mm /15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	550W (AES)
Maximum Power	最大功率:	1100W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	43-2.5k Hz
Voice Coil Diameter	音圈直径:	100mm /4inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ220Ferrite Ring/H25mm

**DF15H01A**

Nominal Diameter	标准直径:	395mm/15 inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	1500W (AES)
Maximum Power	最大功率:	3000W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	40-2k Hz
Voice Coil Diameter	音圈直径:	125mm/5 inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ280Ferrite Ring/H25mm

**DF15H02A**

Nominal Diameter	标准直径:	395mm/15 inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	2000W (AES)
Maximum Power	最大功率:	4000W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	38-2k Hz
Voice Coil Diameter	音圈直径:	150mm/6 inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ300Ferrite Ring/H25mm

**MR15H90**

Nominal Diameter	标准直径:	396mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	400W (AES)
Maximum Power	最大功率:	800W
Sensitivity 1W/1M	灵敏度:	96.5dB
Frequency Range	频响范围:	45-3.6k Hz
Voice Coil Diameter	音圈直径:	75mm/3 inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ190Ferrite Ring/H20mm

**MR15H01**

Nominal Diameter	标准直径:	395mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	400W (AES)
Maximum Power	最大功率:	800W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	55-3.8k Hz
Voice Coil Diameter	音圈直径:	75mm/3 inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ190Ferrite Ring/H20mm

**MR15H72F-A**

Nominal Diameter	标准直径:	393mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	350W (AES)
Maximum Power	最大功率:	700W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	45-3k Hz
Voice Coil Diameter	音圈直径:	75mm/3inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Φ190Ferrite Ring/H20mm

**MR15H36E**

Nominal Diameter	标准直径:	395mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	400W (AES)
Maximum Power	最大功率:	800W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	48-3.5k Hz
Voice Coil Diameter	音圈直径:	75mm/3inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ190Ferrite Ring/H20mm

**MR15H92D-C**

Nominal Diameter	标准直径:	396mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	400W (AES)
Maximum Power	最大功率:	800W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	42-3.5k Hz
Voice Coil Diameter	音圈直径:	75mm/3inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ190Ferrite Ring/H20mm

**MR15H93D-B**

Nominal Diameter	标准直径:	396mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	400W (AES)
Maximum Power	最大功率:	800W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	50-3.5k Hz
Voice Coil Diameter	音圈直径:	75mm/3inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Φ190Ferrite Ring/H25mm

**MR15H82**

Nominal Diameter	标准直径:	397mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	350W (AES)
Maximum Power	最大功率:	700W
Sensitivity 1W/1M	灵敏度:	95dB
Frequency Range	频响范围:	38-4.2k Hz
Voice Coil Diameter	音圈直径:	75mm/3 inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ190Ferrite Ring/H20mm

**MR15H18E**

Nominal Diameter	标准直径:	396mm/15inch
Nominal Impedance	标称阻抗:	4Ω
AES Power Handling	AES功率:	400W (AES)
Maximum Power	最大功率:	800W
Sensitivity 1W/1M	灵敏度:	95dB
Frequency Range	频响范围:	36-1.5k Hz
Voice Coil Diameter	音圈直径:	75mm/3inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ190Ferrite Ring/H20mm

**MR15H36E-W**

Nominal Diameter	标准直径:	396mm / 15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	500W (AES)
Maximum Power	最大功率:	1000W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	46-4.5k Hz
Voice Coil Diameter	音圈直径:	100mm /4inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ220Ferrite Ring/H22mm

**MR15H59D**

Nominal Diameter	标准直径:	396mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	450W (AES)
Maximum Power	最大功率:	900W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	34-2.5k Hz
Voice Coil Diameter	音圈直径:	75mm/3 inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ190*2Ferrite Ring/H20*2mm

**MR15H58D**

Nominal Diameter	标准直径:	396mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	800W (AES)
Maximum Power	最大功率:	1600W
Sensitivity 1W/1M	灵敏度:	95dB
Frequency Range	频响范围:	50-2.5k Hz
Voice Coil Diameter	音圈直径:	100mm/4inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ220*2Ferrite Ring/H20*2mm

**MR15H85C**

Nominal Diameter	标准直径:	396mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	500W (AES)
Maximum Power	最大功率:	1000W
Sensitivity 1W/1M	灵敏度:	95dB
Frequency Range	频响范围:	44-2.8k Hz
Voice Coil Diameter	音圈直径:	100mm/4inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ220Ferrite Ring/H20mm

**MR15H90C**

Nominal Diameter	标准直径:	396mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	500W (AES)
Maximum Power	最大功率:	1000W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	52-4.8k Hz
Voice Coil Diameter	音圈直径:	100mm/4inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ220Ferrite Ring/H25mm

**MR15-2A**

Nominal Diameter	标准直径:	396mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	600W (AES)
Maximum Power	最大功率:	1200W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	56-4k Hz
Voice Coil Diameter	音圈直径:	100mm/4inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Φ220Ferrite Ring/H25mm

**MR15H80A**

Nominal Diameter	标准直径:	396mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	550W (AES)
Maximum Power	最大功率:	1100W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	45-3k Hz
Voice Coil Diameter	音圈直径:	100mm/4 inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ220Ferrite Ring/H25mm

**MR15TBX100**

Nominal Diameter	标准直径:	395mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	800W (AES)
Maximum Power	最大功率:	1600W
Sensitivity 1W/1M	灵敏度:	98dB
Frequency Range	频响范围:	35-2k Hz
Voice Coil Diameter	音圈直径:	100mm/4inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ220Ferrite Ring/H25mm

**MR15TBX100-D**

Nominal Diameter	标准直径:	380mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	600W (AES)
Maximum Power	最大功率:	1200W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	43-2k Hz
Voice Coil Diameter	音圈直径:	100mm/4inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ220Ferrite Ring/H25mm

**MR1520T**

Nominal Diameter	标准直径:	396mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	700W (AES)
Maximum Power	最大功率:	1400W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	43.9-2.6k Hz
Voice Coil Diameter	音圈直径:	100mm/4inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ220Ferrite Ring/H25mm

**MR15H200B**

Nominal Diameter	标准直径:	396mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	800W (AES)
Maximum Power	最大功率:	1600W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	38-2.5k Hz
Voice Coil Diameter	音圈直径:	100mm/4inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ220*2Ferrite Ring/H25*2mm

**MR15H351-H**

Nominal Diameter	标准直径:	393mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	450W (AES)
Maximum Power	最大功率:	900W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	50-2.5k Hz
Voice Coil Diameter	音圈直径:	86mm/3.5inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Φ190Ferrite Ring/H25mm

**MR15-6**

Nominal Diameter	标准直径:	395mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	500W (AES)
Maximum Power	最大功率:	1000W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	44-2.5k Hz
Voice Coil Diameter	音圈直径:	100mm/4inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ220Ferrite Ring/H25mm

**MR15X400**

Nominal Diameter	标准直径:	395mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	550W
Maximum Power	最大功率:	1100W
Sensitivity 1W/1M	灵敏度:	98dB
Frequency Range	频响范围:	49~2.8k Hz
Voice Coil Diameter	音圈直径:	100mm/4inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ220Ferrite Ring/H25mm

**MR15P400**

Nominal Diameter	标准直径:	395mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	550W
Maximum Power	最大功率:	1100W
Sensitivity 1W/1M	灵敏度:	98dB
Frequency Range	频响范围:	43~2k Hz
Voice Coil Diameter	音圈直径:	100mm/4inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ220Ferrite Ring/H25mm

**MR15H86D**

Nominal Diameter	标准直径:	388mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	500W (AES)
Maximum Power	最大功率:	1000W
Sensitivity 1W/1M	灵敏度:	95dB
Frequency Range	频响范围:	48-2.6k Hz
Voice Coil Diameter	音圈直径:	100mm/4inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ220Ferrite Ring/H20mm

**MR15H78C**

Nominal Diameter	标准直径:	389mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	500W (AES)
Maximum Power	最大功率:	1000W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	41-3.8k Hz
Voice Coil Diameter	音圈直径:	100mm/4inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Φ220*2Ferrite Ring/H25*2mm

**MRJ15S**

Nominal Diameter	标准直径:	380mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	600W
Maximum Power	最大功率:	1200W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	52-2.6k Hz
Voice Coil Diameter	音圈直径:	100mm/4inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ220*2Ferrite Ring/H25*2mm

**MRJ15**

Nominal Diameter	标准直径:	380mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	500W
Maximum Power	最大功率:	1000W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	50-3.3k Hz
Voice Coil Diameter	音圈直径:	100mm/4inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ220Ferrite Ring/H25mm

**MR15H33D**

Nominal Diameter	标准直径:	390mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	400W (AES)
Maximum Power	最大功率:	800W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	39-4kHz
Voice Coil Diameter	音圈直径:	75mm/3 inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ156*2Ferrite Ring/H20*2mm

**MR15H75J**

Nominal Diameter	标准直径:	380mm/15 inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	400W
Maximum Power	最大功率:	800W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	43-3.3k Hz
Voice Coil Diameter	音圈直径:	75mm/3 inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ190Ferrite Ring/H20mm

**MR15H26E**

Nominal Diameter	标准直径:	389mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	350W (AES)
Maximum Power	最大功率:	700W
Sensitivity 1W/1M	灵敏度:	95dB
Frequency Range	频响范围:	42-4k Hz
Voice Coil Diameter	音圈直径:	75mm/3inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ190Ferrite Ring/H20mm

**MR15H06B**

Nominal Diameter	标准直径:	390mm/15 inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	400W (AES)
Maximum Power	最大功率:	800W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	48-3.2k Hz
Voice Coil Diameter	音圈直径:	75mm/3 inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ190Ferrite Ring/H20mm

**MR15H22D**

Nominal Diameter	标准直径:	395mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	350W (AES)
Maximum Power	最大功率:	700W
Sensitivity 1W/1M	灵敏度:	95dB
Frequency Range	频响范围:	34-5k Hz
Voice Coil Diameter	音圈直径:	75mm/3 inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ190Ferrite Ring/H20mm

**MR15-8A**

Nominal Diameter	标准直径:	382mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	400W (AES)
Maximum Power	最大功率:	800W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	43-3.5k Hz
Voice Coil Diameter	音圈直径:	75mm/3inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Φ200Ferrite Ring/H20mm

**MR15H73C**

Nominal Diameter	标准直径:	389mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	400W (AES)
Maximum Power	最大功率:	800W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	47-3.7k Hz
Voice Coil Diameter	音圈直径:	75mm/3inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ190Ferrite Ring/H20mm

**MR15H23E-16**

Nominal Diameter	标准直径:	395mm/15inch
Nominal Impedance	标称阻抗:	16Ω
AES Power Handling	AES功率:	200W (AES)
Maximum Power	最大功率:	400W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	66-18k Hz
Voice Coil Diameter	音圈直径:	50mm/2inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Φ190Ferrite Ring/H20mm

**MR15H16E**

Nominal Diameter	标准直径:	395mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	450W (AES)
Maximum Power	最大功率:	900W
Sensitivity 1W/1M	灵敏度:	99dB
Frequency Range	频响范围:	50-4.5k Hz
Voice Coil Diameter	音圈直径:	75mm/3inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Φ200Ferrite Ring/H25mm

**MR15H79D**

Nominal Diameter	标准直径:	395mm/15 inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	500W (AES)
Maximum Power	最大功率:	1000W
Sensitivity 1W/1M	灵敏度:	98dB
Frequency Range	频响范围:	56-4k Hz
Voice Coil Diameter	音圈直径:	100mm/4 inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Φ220Ferrite Ring/H25mm

**MR15H90B**

Nominal Diameter	标准直径:	395mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	500W (AES)
Maximum Power	最大功率:	1000W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	39-3.5k Hz
Voice Coil Diameter	音圈直径:	100mm/4inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ220Ferrite Ring/H25mm

**MR15TBW100**

Nominal Diameter	标准直径:	395mm/15 inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	800W (AES)
Maximum Power	最大功率:	1600W
Sensitivity 1W/1M	灵敏度:	98dB
Frequency Range	频响范围:	35-2k Hz
Voice Coil Diameter	音圈直径:	100mm/4 inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ220Ferrite Ring/H25mm

**MR15H01FT**

Nominal Diameter	标准直径 :	395mm/15inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	700W (AES)
Maximum Power	最大功率 :	1400W
Sensitivity 1W/1M	灵敏度 :	96dB
Frequency Range	频响范围 :	53-3.5k Hz
Voice Coil Diameter	音圈直径 :	100mm/4inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ220Ferrite Ring/H25mm

**MR15H57D**

Nominal Diameter	标准直径 :	390mm/15inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	800W (AES)
Maximum Power	最大功率 :	1600W
Sensitivity 1W/1M	灵敏度 :	95dB
Frequency Range	频响范围 :	70-1.8k Hz
Voice Coil Diameter	音圈直径 :	115mm/4.5inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ220*2Ferrite Ring/H25*2mm

**MR15H61D**

Nominal Diameter	标准直径 :	402mm/15inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	1200W (AES)
Maximum Power	最大功率 :	2400W
Sensitivity 1W/1M	灵敏度 :	96dB
Frequency Range	频响范围 :	53-2.5k Hz
Voice Coil Diameter	音圈直径 :	125mm/5inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ280Ferrite Ring/H25mm

**MR15H55C**

Nominal Diameter	标准直径 :	390mm/15inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	1000W (AES)
Maximum Power	最大功率 :	2000W
Sensitivity 1W/1M	灵敏度 :	95dB
Frequency Range	频响范围 :	44-2.2k Hz
Voice Coil Diameter	音圈直径 :	115mm/4.5 inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ253Ferrite Ring/H25mm

**MR15H42E**

Nominal Diameter	标准直径 :	390mm/15inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	1200W (AES)
Maximum Power	最大功率 :	2400W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	39-2k Hz
Voice Coil Diameter	音圈直径 :	125mm/5inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ253*2Ferrite Ring/H20*2mm

**MR15HF078A-01**

Nominal Diameter	标准直径 :	380mm/15 inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	1200W (AES)
Maximum Power	最大功率 :	2400W
Sensitivity 1W/1M	灵敏度 :	95dB
Frequency Range	频响范围 :	46-2.2k Hz
Voice Coil Diameter	音圈直径 :	125mm/5inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ280Ferrite Ring/H25mm

**MR15H67D**

Nominal Diameter	标准直径 :	390mm/15inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	1400W (AES)
Maximum Power	最大功率 :	2800W
Sensitivity 1W/1M	灵敏度 :	96dB
Frequency Range	频响范围 :	46-2k HZ
Voice Coil Diameter	音圈直径 :	150mm/6inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ330*2Ferrite Ring/H25*5mm

**MR15H19E**

Nominal Diameter	标准直径 :	390mm/15inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	2600W (AES)
Maximum Power	最大功率 :	5200W
Sensitivity 1W/1M	灵敏度 :	96dB
Frequency Range	频响范围 :	98-1.5k Hz
Voice Coil Diameter	音圈直径 :	150mm/6inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ330*5Ferrite Ring/H25*5mm

**MR15N98D**

Nominal Diameter	标准直径 :	385mm/15inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	400W (AES)
Maximum Power	最大功率 :	800W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	52-5k Hz
Voice Coil Diameter	音圈直径 :	75mm/3inch
Winding Material	线材 :	Aluminium
Magnet	磁体 :	Neodymium Ring

**MR15N75C-A**

Nominal Diameter	标准直径 :	389mm/15inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	400W (AES)
Maximum Power	最大功率 :	800W
Sensitivity 1W/1M	灵敏度 :	98dB
Frequency Range	频响范围 :	42-3.6k Hz
Voice Coil Diameter	音圈直径 :	75mm/3 inch
Winding Material	线材 :	Aluminium
Magnet	磁体 :	Neodymium Ring

**TS15N09A**

Nominal Diameter	标准直径 :	395mm/15inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	600W (AES)
Maximum Power	最大功率 :	1200W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	45-3k Hz
Voice Coil Diameter	音圈直径 :	100mm/4inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Neodymium Ring

**JY15N09A**

Nominal Diameter	标准直径 :	395mm / 15inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	600W (AES)
Maximum Power	最大功率 :	1200W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	45-2.5k Hz
Voice Coil Diameter	音圈直径 :	100mm /4inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Neodymium Ring

15"

PROFESSIONAL SPEAKER SERIES



MR15N2226

Nominal Diameter	标准直径:	390mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	500W (AES)
Maximum Power	最大功率:	1000W
Sensitivity 1W/1M	灵敏度:	95dB
Frequency Range	频响范围:	42-3k Hz
Voice Coil Diameter	音圈直径:	75mm/3inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Neodymium Ring



MR15N16E

Nominal Diameter	标准直径:	392mm / 15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	450W (AES)
Maximum Power	最大功率:	900W
Sensitivity 1W/1M	灵敏度:	98dB
Frequency Range	频响范围:	45-4.5k Hz
Voice Coil Diameter	音圈直径:	75mm /3inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Neodymium Ring



MR15N01E-A

Nominal Diameter	标准直径:	392mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	400W (AES)
Maximum Power	最大功率:	800W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	45-3.5k Hz
Voice Coil Diameter	音圈直径:	75mm/3inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Neodymium Ring

Fiber



MR15N06E

Nominal Diameter	标准直径:	395mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	400W (AES)
Maximum Power	最大功率:	800W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	55-6k Hz
Voice Coil Diameter	音圈直径:	75mm/3inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Neodymium Ring



MR15NDL88A

Nominal Diameter	标准直径:	395mm / 15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	500W (AES)
Maximum Power	最大功率:	1000W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	51-3.5k Hz
Voice Coil Diameter	音圈直径:	86mm /3.5inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Neodymium Ring



MR15N03E

Nominal Diameter	标准直径:	393mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	600W (AES)
Maximum Power	最大功率:	1200W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	44-2.5k Hz
Voice Coil Diameter	音圈直径:	100mm/4inch
Winding Material	线材:	Copper
Magnet	磁体:	Neodymium Ring



MR15NW115

Nominal Diameter	标准直径:	395mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	800W (AES)
Maximum Power	最大功率:	1600W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	40-2.5k Hz
Voice Coil Diameter	音圈直径:	115mm/4.5inch
Winding Material	线材:	Copper
Magnet	磁体:	Neodymium Ring



MR15NA100

Nominal Diameter	标准直径:	395mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	600W (AES)
Maximum Power	最大功率:	1200W
Sensitivity 1W/1M	灵敏度:	98dB
Frequency Range	频响范围:	45-2.5k Hz
Voice Coil Diameter	音圈直径:	100mm /4inch
Winding Material	线材:	Copper
Magnet	磁体:	Neodymium Ring



MR15N02E

Nominal Diameter	标准直径:	396mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	500W (AES)
Maximum Power	最大功率:	1000W
Sensitivity 1W/1M	灵敏度:	98dB
Frequency Range	频响范围:	46-2.5k Hz
Voice Coil Diameter	音圈直径:	100mm/4inch
Winding Material	线材:	Copper
Magnet	磁体:	Neodymium Ring



MR15N351

Nominal Diameter	标准直径:	393mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	450W (AES)
Maximum Power	最大功率:	900W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	44-3.5k Hz
Voice Coil Diameter	音圈直径:	86mm/3.5 inch
Winding Material	线材:	Copper
Magnet	磁体:	Neodymium Ring



MR15N05E

Nominal Diameter	标准直径:	392mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	700W (AES)
Maximum Power	最大功率:	1400W
Sensitivity 1W/1M	灵敏度:	98dB
Frequency Range	频响范围:	47-3k Hz
Voice Coil Diameter	音圈直径:	100mm/4inch
Winding Material	线材:	Copper
Magnet	磁体:	Neodymium Ring



MR15N401

Nominal Diameter	标准直径:	392mm/15 inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	550W
Maximum Power	最大功率:	1100W
Sensitivity 1W/1M	灵敏度:	98dB
Frequency Range	频响范围:	42-2.3k Hz
Voice Coil Diameter	音圈直径:	100mm/4 inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Neodymium Ring

**BH18H01**

Nominal Diameter	标准直径:	465mm/18inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	800W (AES)
Maximum Power	最大功率:	1600W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	35-4k Hz
Voice Coil Diameter	音圈直径:	100mm/4inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ220Ferrite Ring/H25mm

**BH18H02**

Nominal Diameter	标准直径:	465mm/18inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	1000W (AES)
Maximum Power	最大功率:	2000W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	38-2k Hz
Voice Coil Diameter	音圈直径:	115mm/4.5inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ253Ferrite Ring/H25mm

**BH18H03**

Nominal Diameter	标准直径:	466mm/18inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	1200W (AES)
Maximum Power	最大功率:	2400W
Sensitivity 1W/1M	灵敏度:	98dB
Frequency Range	频响范围:	40-2k Hz
Voice Coil Diameter	音圈直径:	125mm/5inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ280Ferrite Ring/H25mm

**BH18H10**

Nominal Diameter	标准直径:	465mm /18inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	1400W (AES)
Maximum Power	最大功率:	2800W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	40-1.5k Hz
Voice Coil Diameter	音圈直径:	125mm /5inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ253*2Ferrite Ring/H20*2mm

**BH18H09**

Nominal Diameter	标准直径:	465mm /18 inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	1200W (AES)
Maximum Power	最大功率:	2400W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	40-2k Hz
Voice Coil Diameter	音圈直径:	125mm / 5inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ280Ferrite Ring/H25mm

**BH18H05**

Nominal Diameter	标准直径:	466mm/18inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	1800W (AES)
Maximum Power	最大功率:	3600W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	46-2k Hz
Voice Coil Diameter	音圈直径:	150mm/6inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ330Ferrite Ring/H25mm

**MR18H09D**

Nominal Diameter	标准直径:	466mm/18 inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	700W (AES)
Maximum Power	最大功率:	1400W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	35-2k Hz
Voice Coil Diameter	音圈直径:	100mm/4 inch
Winding Material	线材:	copper
Magnet	磁体:	Φ220Ferrite Ring/H25mm

**MR18H86D**

Nominal Diameter	标准直径:	462mm/18 inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	600W (AES)
Maximum Power	最大功率:	1200W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	42-3k Hz
Voice Coil Diameter	音圈直径:	100mm/4 inch
Winding Material	线材:	copper
Magnet	磁体:	Φ220Ferrite Ring/H20mm

**MR18H87D**

Nominal Diameter	标准直径:	462mm/18 inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	800W (AES)
Maximum Power	最大功率:	1600W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	39-2.5k Hz
Voice Coil Diameter	音圈直径:	100mm/4 inch
Winding Material	线材:	copper
Magnet	磁体:	Φ220Ferrite Ring/H25mm

**JY18H03**

Nominal Diameter	标准直径:	465mm / 18inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	1200W (AES)
Maximum Power	最大功率:	2400W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	42-2k Hz
Voice Coil Diameter	音圈直径:	125mm / 5inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ280Ferrite Ring/H25mm

**DF18H01A**

Nominal Diameter	标准直径:	470mm/18inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	2000W (AES)
Maximum Power	最大功率:	4000W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	40-1.5k Hz
Voice Coil Diameter	音圈直径:	150mm/6inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ330Ferrite Ring/H30mm

**DF18H02A**

Nominal Diameter	标准直径:	470mm/18inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	3000W (AES)
Maximum Power	最大功率:	6000W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	35-1.5k Hz
Voice Coil Diameter	音圈直径:	200mm/8inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ380Ferrite Ring/H25*2mm

**EL18-20C**

Nominal Diameter	标准直径:	460mm/18inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	800W (AES)
Maximum Power	最大功率:	1600W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	50-3k Hz
Voice Coil Diameter	音圈直径:	100mm/4 inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ220Ferrite Ring/H25mm

**TS18H220C**

Nominal Diameter	标准直径:	460mm/18inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	800W (AES)
Maximum Power	最大功率:	1600W
Sensitivity 1W/1M	灵敏度:	98dB
Frequency Range	频响范围:	45-3k Hz
Voice Coil Diameter	音圈直径:	100mm/4inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ220Ferrite Ring/H25mm

**TS18H05A**

Nominal Diameter	标准直径:	466mm/18inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	1300W (AES)
Maximum Power	最大功率:	2600W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	39-2k Hz
Voice Coil Diameter	音圈直径:	125mm/5inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ253*2Ferrite Ring/H20*2mm

**MR18H65D**

Nominal Diameter	标准直径:	466mm/18inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	1200W (AES)
Maximum Power	最大功率:	2400W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	46-3k Hz
Voice Coil Diameter	音圈直径:	125mm/5inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ280Ferrite Ring/H25mm

**TS18H08A-A**

Nominal Diameter	标准直径:	466mm/18inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	1300W (AES)
Maximum Power	最大功率:	2600W
Sensitivity 1W/1M	灵敏度:	98.5dB
Frequency Range	频响范围:	42-2k Hz
Voice Coil Diameter	音圈直径:	125mm/5inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ280Ferrite Ring/H25mm

**TS18H15A**

Nominal Diameter	标准直径:	465mm/18inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	1800W (AES)
Maximum Power	最大功率:	3600W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	43-2k Hz
Voice Coil Diameter	音圈直径:	150mm/6inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ280Ferrite Ring/H25mm

**MR18H90**

Nominal Diameter	标准直径:	460mm/18inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	800W (AES)
Maximum Power	最大功率:	1600W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	34-2.5k Hz
Voice Coil Diameter	音圈直径:	100mm/4 inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ220Ferrite Ring/H25mm

**MR18TBX100-8**

Nominal Diameter	标准直径:	460mm/18 inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	800W (AES)
Maximum Power	最大功率:	1600W
Sensitivity 1W/1M	灵敏度:	98dB
Frequency Range	频响范围:	40-3k Hz
Voice Coil Diameter	音圈直径:	100mm/4inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ220Ferrite Ring/H25mm

**MR18H95C**

Nominal Diameter	标准直径:	460mm/18inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	600W (AES)
Maximum Power	最大功率:	1200W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	36-2.9k Hz
Voice Coil Diameter	音圈直径:	100mm/4 inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ220Ferrite Ring/H25mm

**MR18H11D-A**

Nominal Diameter	标准直径:	462mm/18inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	600W (AES)
Maximum Power	最大功率:	1200W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	39-2.5k HZ
Voice Coil Diameter	音圈直径:	100mm/4inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ220Ferrite Ring/H25mm

**MR18-42A**

Nominal Diameter	标准直径:	460mm/18 inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	600W
Maximum Power	最大功率:	1200W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	41-2.7k Hz
Voice Coil Diameter	音圈直径:	100mm/4 inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ220Ferrite Ring/H20mm

**MR18H36E**

Nominal Diameter	标准直径:	460mm/18inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	650W (AES)
Maximum Power	最大功率:	1300W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	40-2.5k Hz
Voice Coil Diameter	音圈直径:	100mm/4inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ220Ferrite Ring/H25mm

**MR18H02D**

Nominal Diameter	标准直径:	466mm/18inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	800W (AES)
Maximum Power	最大功率:	1600W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	37-2.4k HZ
Voice Coil Diameter	音圈直径:	100mm/4inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ220*2Ferrite Ring/H25*2mm

**MR18H33D**

Nominal Diameter	标准直径:	461mm/18inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	1000W (AES)
Maximum Power	最大功率:	2000W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	45-2.5k Hz
Voice Coil Diameter	音圈直径:	100mm/4inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ220*2Ferrite Ring/H25*2mm

**MR18H32D**

Nominal Diameter	标准直径:	461mm/18inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	1000W (AES)
Maximum Power	最大功率:	2000W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	45-1.8k Hz
Voice Coil Diameter	音圈直径:	115mm /4.5inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ220*2Ferrite Ring/H25*2mm

**MR18P300**

Nominal Diameter	标准直径:	460mm/18inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	700W (AES)
Maximum Power	最大功率:	1400W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	39-3.2k Hz
Voice Coil Diameter	音圈直径:	100mm/4 inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ220Ferrite Ring/H25mm

**MR18P400**

Nominal Diameter	标准直径:	460mm/18 inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	800W
Maximum Power	最大功率:	1600W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	38-2.5k Hz
Voice Coil Diameter	音圈直径:	100mm/4 inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ220Ferrite Ring/H25mm

**MR18G401**

Nominal Diameter	标准直径:	460mm/18inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	800W
Maximum Power	最大功率:	1600W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	36-2.5k Hz
Voice Coil Diameter	音圈直径:	100mm/4 inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ220Ferrite Ring/H20mm

**MR18-5D**

Nominal Diameter	标准直径:	466mm/18 inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	800W (AES)
Maximum Power	最大功率:	1600W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	41.3~2.6k Hz
Voice Coil Diameter	音圈直径:	100mm/4 inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ220Ferrite Ring/H25mm

**MR18SW21A-02**

Nominal Diameter	标准直径:	460mm/18inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	1200W (AES)
Maximum Power	最大功率:	2400W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	45-2.9k Hz
Voice Coil Diameter	音圈直径:	115mm/4.5 inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ253Ferrite Ring/H30mm

**MR18H55D**

Nominal Diameter	标准直径:	466mm/18inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	1000W (AES)
Maximum Power	最大功率:	2000W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	40-2k Hz
Voice Coil Diameter	音圈直径:	115mm/4.5inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ253Ferrite Ring/H25mm

**MR18H86E**

Nominal Diameter	标准直径:	460mm/18inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	700W (AES)
Maximum Power	最大功率:	1400W
Sensitivity 1W/1M	灵敏度:	95dB
Frequency Range	频响范围:	37-2.8k HZ
Voice Coil Diameter	音圈直径:	100mm/4inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ220Ferrite Ring/H30mm

**MR18TBW100**

Nominal Diameter	标准直径:	460mm/18 inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	900W (AES)
Maximum Power	最大功率:	1800W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	36~1.8K Hz
Voice Coil Diameter	音圈直径:	100mm/4 inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ220Ferrite Ring/H25mm

**MR18H85C**

Nominal Diameter	标准直径:	460mm/18inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	900W (AES)
Maximum Power	最大功率:	1800W
Sensitivity 1W/1M	灵敏度:	98dB
Frequency Range	频响范围:	38-3k Hz
Voice Coil Diameter	音圈直径:	100mm/4inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ220Ferrite Ring/H25mm

**MR18H01FT**

Nominal Diameter	标准直径 :	460mm/18inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	1000W (AES)
Maximum Power	最大功率 :	2000W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	36-3k Hz
Voice Coil Diameter	音圈直径 :	100mm/4inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ220Ferrite Ring/H30mm

**MR18H02FT**

Nominal Diameter	标准直径 :	460mm/18inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	800W (AES)
Maximum Power	最大功率 :	1600W
Sensitivity 1W/1M	灵敏度 :	95dB
Frequency Range	频响范围 :	40-2.5k Hz
Voice Coil Diameter	音圈直径 :	100mm/4inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ220Ferrite Ring/H25mm

**MR280-1**

Nominal Diameter	标准直径 :	460mm/18inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	1300W
Maximum Power	最大功率 :	2600W
Sensitivity 1W/1M	灵敏度 :	96dB
Frequency Range	频响范围 :	40-2.2k Hz
Voice Coil Diameter	音圈直径 :	125mm/5 inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ280Ferrite Ring/H25mm

**MR18-15B**

Nominal Diameter	标准直径 :	460mm/18inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	700W (AES)
Maximum Power	最大功率 :	1400W
Sensitivity 1W/1M	灵敏度 :	96dB
Frequency Range	频响范围 :	39.2-2.8k Hz
Voice Coil Diameter	音圈直径 :	100mm/4 inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ220Ferrite Ring/H20mm

**MR18-15BS**

Nominal Diameter	标准直径 :	460mm/18 inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	900W (AES)
Maximum Power	最大功率 :	1800W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	38-2.3k Hz
Voice Coil Diameter	音圈直径 :	100mm/4 inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ220*2Ferrite Ring/H20*2mm

**MR18-33A-A**

Nominal Diameter	标准直径 :	464mm/18inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	1500W (AES)
Maximum Power	最大功率 :	3000W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	45-2.5k Hz
Voice Coil Diameter	音圈直径 :	125mm/5inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ280Ferrite Ring/H25mm

**MR1850-A**

Nominal Diameter	标准直径 :	470mm/18 inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	1200W
Maximum Power	最大功率 :	2400W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	38-1.9k Hz
Voice Coil Diameter	音圈直径 :	125mm/5inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ280Ferrite Ring/H25mm

**MR1850-J**

Nominal Diameter	标准直径 :	470mm/18 inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	1200W (AES)
Maximum Power	最大功率 :	2400W
Sensitivity 1W/1M	灵敏度 :	96dB
Frequency Range	频响范围 :	46-2k Hz
Voice Coil Diameter	音圈直径 :	125mm/5 inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ280Ferrite Ring/H25mm

**PD1850**

Nominal Diameter	标准直径 :	470mm/18inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	1200W (AES)
Maximum Power	最大功率 :	2400W
Sensitivity 1W/1M	灵敏度 :	96dB
Frequency Range	频响范围 :	44-2k Hz
Voice Coil Diameter	音圈直径 :	125mm/5 inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ280Ferrite Ring/H25mm

**MR18H91C**

Nominal Diameter	标准直径 :	460mm/18inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	1400W (AES)
Maximum Power	最大功率 :	2800W
Sensitivity 1W/1M	灵敏度 :	96dB
Frequency Range	频响范围 :	40-4k Hz
Voice Coil Diameter	音圈直径 :	125mm/5inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ280Ferrite Ring/H25mm

**MR18H45D**

Nominal Diameter	标准直径 :	471mm/18inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	1400W (AES)
Maximum Power	最大功率 :	2800W
Sensitivity 1W/1M	灵敏度 :	94dB
Frequency Range	频响范围 :	45-2k Hz
Voice Coil Diameter	音圈直径 :	150mm/6inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ280Ferrite Ring/H30mm

**MR18H28D**

Nominal Diameter	标准直径 :	460mm/18inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	1200W (AES)
Maximum Power	最大功率 :	2400W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	50-1.5k Hz
Voice Coil Diameter	音圈直径 :	125mm/5inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ280Ferrite Ring/H25mm

**MR18-29B**

Nominal Diameter	标准直径 :	466mm/18 inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	1200W
Maximum Power	最大功率 :	2400W
Sensitivity 1W/1M	灵敏度 :	96dB
Frequency Range	频响范围 :	34-1.8k Hz
Voice Coil Diameter	音圈直径 :	125mm/5 inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ280Ferrite Ring/H25mm

**MR18-29C**

Nominal Diameter	标准直径 :	466mm/18inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	1300W (AES)
Maximum Power	最大功率 :	2600W
Sensitivity 1W/1M	灵敏度 :	96dB
Frequency Range	频响范围 :	40-2.3k Hz
Voice Coil Diameter	音圈直径 :	125mm/5 inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ280*2Ferrite Ring/H20*2mm

**MR18H83C-D**

Nominal Diameter	标准直径 :	470mm/18inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	1800W (AES)
Maximum Power	最大功率 :	3600W
Sensitivity 1W/1M	灵敏度 :	96dB
Frequency Range	频响范围 :	40-1.5k Hz
Voice Coil Diameter	音圈直径 :	150mm/6inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ330Ferrite Ring/H30mm

**MR18H83C-H**

Nominal Diameter	标准直径 :	470mm/18inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	2000W (AES)
Maximum Power	最大功率 :	4000W
Sensitivity 1W/1M	灵敏度 :	95dB
Frequency Range	频响范围 :	42-1.5k Hz
Voice Coil Diameter	音圈直径 :	150mm/6inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ330Ferrite Ring/H30mm

**MR18H83C-J**

Nominal Diameter	标准直径 :	465mm/18inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	1500W (AES)
Maximum Power	最大功率 :	3000W
Sensitivity 1W/1M	灵敏度 :	95dB
Frequency Range	频响范围 :	40-1.5k Hz
Voice Coil Diameter	音圈直径 :	150mm/6inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ280*2Ferrite Ring/H20*2mm

**MR18H57D**

Nominal Diameter	标准直径 :	470mm/18inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	1500W (AES)
Maximum Power	最大功率 :	3000W
Sensitivity 1W/1M	灵敏度 :	95dB
Frequency Range	频响范围 :	42-1.5k HZ
Voice Coil Diameter	音圈直径 :	140mm/5.5inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ300*2Ferrite Ring/H20*2mm

**MR18H97C**

Nominal Diameter	标准直径 :	465mm/18inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	2000W (AES)
Maximum Power	最大功率 :	4000W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	50-1.6k Hz
Voice Coil Diameter	音圈直径 :	150mm/6inch
Winding Material	线材 :	PISV
Magnet	磁体 :	Φ300*3Ferrite Ring/H20*3mm

**MR18NW100-8**

Nominal Diameter	标准直径 :	460mm/18inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	900W (AES)
Maximum Power	最大功率 :	1800W
Sensitivity 1W/1M	灵敏度 :	98dB
Frequency Range	频响范围 :	40-3k Hz
Voice Coil Diameter	音圈直径 :	100mm/4inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Neodymium Ring

**MR18N100T**

Nominal Diameter	标准直径 :	460mm/18 inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	800W
Maximum Power	最大功率 :	1600W
Sensitivity 1W/1M	灵敏度 :	95.9dB
Frequency Range	频响范围 :	35-2.7k Hz
Voice Coil Diameter	音圈直径 :	100mm/4 inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Neodymium Ring

**MR18N401**

Nominal Diameter	标准直径 :	460mm/18 inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	800W
Maximum Power	最大功率 :	1600W
Sensitivity 1W/1M	灵敏度 :	98.2dB
Frequency Range	频响范围 :	37-2.3k Hz
Voice Coil Diameter	音圈直径 :	100mm/4 inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Neodymium Ring

**MR18N451**

Nominal Diameter	标准直径 :	465mm/18inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	1000W (AES)
Maximum Power	最大功率 :	2000W
Sensitivity 1W/1M	灵敏度 :	96dB
Frequency Range	频响范围 :	43-3k Hz
Voice Coil Diameter	音圈直径 :	115mm/4.5 inch
Winding Material	线材 :	Aluminium
Magnet	磁体 :	Neodymium Ring

**MR18N01E**

Nominal Diameter	标准直径 :	462mm/18inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	700W (AES)
Maximum Power	最大功率 :	1400W
Sensitivity 1W/1M	灵敏度 :	98dB
Frequency Range	频响范围 :	42-2k Hz
Voice Coil Diameter	音圈直径 :	100mm/4inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Neodymium Ring

**MR18N16D**

Nominal Diameter	标准直径 :	462mm/18inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	1000W (AES)
Maximum Power	最大功率 :	2000W
Sensitivity 1W/1M	灵敏度 :	96dB
Frequency Range	频响范围 :	40-1.5k Hz
Voice Coil Diameter	音圈直径 :	100mm /4inch
Winding Material	线 材 :	Copper
Magnet	磁 体 :	Neodymium Ring

**TS18N09B**

Nominal Diameter	标准直径 :	466mm/18inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	900W (AES)
Maximum Power	最大功率 :	1800W
Sensitivity 1W/1M	灵敏度 :	98dB
Frequency Range	频响范围 :	40-2.5k Hz
Voice Coil Diameter	音圈直径 :	100mm/4inch
Winding Material	线 材 :	Copper
Magnet	磁 体 :	Neodymium Ring

**TS18N09A**

Nominal Diameter	标准直径 :	466mm/18inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	1200W (AES)
Maximum Power	最大功率 :	2400W
Sensitivity 1W/1M	灵敏度 :	98dB
Frequency Range	频响范围 :	40-1.5k Hz
Voice Coil Diameter	音圈直径 :	125mm/5inch
Winding Material	线 材 :	Copper
Magnet	磁 体 :	Neodymium Ring

**MR18N03E**

Nominal Diameter	标准直径 :	460mm/18inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	900W (AES)
Maximum Power	最大功率 :	1800W
Sensitivity 1W/1M	灵敏度 :	98dB
Frequency Range	频响范围 :	39-3k Hz
Voice Coil Diameter	音圈直径 :	100mm/4inch
Winding Material	线 材 :	Copper
Magnet	磁 体 :	Neodymium Ring

**MR18SW115**

Nominal Diameter	标准直径 :	460mm/18 inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	1100W
Maximum Power	最大功率 :	2200W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	38-1.3k Hz
Voice Coil Diameter	音圈直径 :	115mm/4.5 inch
Winding Material	线 材 :	Copper
Magnet	磁 体 :	Neodymium Ring

**MR18N115-8**

Nominal Diameter	标准直径 :	460mm/18inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	1000W (AES)
Maximum Power	最大功率 :	2000W
Sensitivity 1W/1M	灵敏度 :	96dB
Frequency Range	频响范围 :	38-2.5k HZ
Voice Coil Diameter	音圈直径 :	115mm/4.5inch
Winding Material	线 材 :	Copper
Magnet	磁 体 :	Neodymium Ring

**MR18SW115G-A**

Nominal Diameter	标准直径 :	460mm/18inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	1100W (AES)
Maximum Power	最大功率 :	2200W
Sensitivity 1W/1M	灵敏度 :	98dB
Frequency Range	频响范围 :	40-2.1k Hz
Voice Coil Diameter	音圈直径 :	115mm/4.5 inch
Winding Material	线 材 :	Copper
Magnet	磁 体 :	Neodymium Ring

**MR18N98D**

Nominal Diameter	标准直径 :	460mm/18inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	1000W (AES)
Maximum Power	最大功率 :	2000W
Sensitivity 1W/1M	灵敏度 :	98dB
Frequency Range	频响范围 :	39-1.5k Hz
Voice Coil Diameter	音圈直径 :	115mm/4.5inch
Winding Material	线 材 :	Copper
Magnet	磁 体 :	Neodymium Ring

**MR18N16E**

Nominal Diameter	标准直径 :	460mm / 18inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	1400W (AES)
Maximum Power	最大功率 :	2800W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	41-2k Hz
Voice Coil Diameter	音圈直径 :	125mm /5inch
Winding Material	线 材 :	Copper
Magnet	磁 体 :	Neodymium Ring

**MR18N02E**

Nominal Diameter	标准直径 :	460mm/18inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	1200W (AES)
Maximum Power	最大功率 :	2400W
Sensitivity 1W/1M	灵敏度 :	98dB
Frequency Range	频响范围 :	38-2k Hz
Voice Coil Diameter	音圈直径 :	125mm/5inch
Winding Material	线 材 :	Copper
Magnet	磁 体 :	Neodymium Ring

**MR18N83C**

Nominal Diameter	标准直径 :	470mm/18inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	1800W (AES)
Maximum Power	最大功率 :	3600W
Sensitivity 1W/1M	灵敏度 :	97dB
Frequency Range	频响范围 :	40-1.8k Hz
Voice Coil Diameter	音圈直径 :	152mm/6inch
Winding Material	线 材 :	Copper
Magnet	磁 体 :	Neodymium Ring

**MR18N83D**

Nominal Diameter	标准直径 :	470mm/18inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	1800W (AES)
Maximum Power	最大功率 :	3600W
Sensitivity 1W/1M	灵敏度 :	96dB
Frequency Range	频响范围 :	40-1.8k Hz
Voice Coil Diameter	音圈直径 :	152mm/6inch
Winding Material	线 材 :	Copper
Magnet	磁 体 :	Neodymium Ring

**MR21H07C**

Nominal Diameter	标准直径:	548mm/21inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	1400W (AES)
Maximum Power	最大功率:	2800W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	25-2.5k Hz
Voice Coil Diameter	音圈直径:	115mm/4.5 inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ253Ferrite Ring/H25mm

**MR21-2**

Nominal Diameter	标准直径:	545mm/21inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	1800W (AES)
Maximum Power	最大功率:	3600W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	38-2.7k Hz
Voice Coil Diameter	音圈直径:	152mm/6inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ300Ferrite Ring/H30mm

**MR21H13C**

Nominal Diameter	标准直径:	545mm/21inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	2000W (AES)
Maximum Power	最大功率:	4000W
Sensitivity 1W/1M	灵敏度:	95dB
Frequency Range	频响范围:	36-1.8k Hz
Voice Coil Diameter	音圈直径:	150mm/6inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Φ330Ferrite Ring/H25mm

**MR21H06C**

Nominal Diameter	标准直径:	570mm/21inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	1800W (AES)
Maximum Power	最大功率:	3600W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	39-1.7k Hz
Voice Coil Diameter	音圈直径:	150mm/6 inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ330*2Ferrite Ring/H20*2mm

**DF21H01A**

Nominal Diameter	标准直径:	545mm/21inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	4000W (AES)
Maximum Power	最大功率:	8000W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	30-1.5k Hz
Voice Coil Diameter	音圈直径:	200mm/8inch
Winding Material	线材:	Aluminum
Magnet	磁体:	Φ380*2Ferrite Ring/H25*2mm

**DF21H03A**

Nominal Diameter	标准直径:	545mm/21inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	2500W (AES)
Maximum Power	最大功率:	5000W
Sensitivity 1W/1M	灵敏度:	98dB
Frequency Range	频响范围:	28-1.5k Hz
Voice Coil Diameter	音圈直径:	150mm/6inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ330Ferrite Ring/H30mm

**MR21H02C**

Nominal Diameter	标准直径:	570mm/21inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	1800W (AES)
Maximum Power	最大功率:	3600W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	32-1.7k Hz
Voice Coil Diameter	音圈直径:	150mm/6 inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ330*2Ferrite Ring/H20*2mm

**MR21H09C**

Nominal Diameter	标准直径:	545mm/21inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	4500W (AES)
Maximum Power	最大功率:	9000W
Sensitivity 1W/1M	灵敏度:	95dB
Frequency Range	频响范围:	41-1.2k Hz
Voice Coil Diameter	音圈直径:	203mm/8 inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ380*4Ferrite Ring/H25*4mm

**MR21H16C**

Nominal Diameter	标准直径:	545mm/21inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	6000W (AES)
Maximum Power	最大功率:	12000W
Sensitivity 1W/1M	灵敏度:	95dB
Frequency Range	频响范围:	44-1.5k Hz
Voice Coil Diameter	音圈直径:	200mm/8inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ380*4Ferrite Ring/H30*4mm

**MR21N01**

Nominal Diameter	标准直径:	550mm/21inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	1500W (AES)
Maximum Power	最大功率:	3000W
Sensitivity 1W/1M	灵敏度:	95dB
Frequency Range	频响范围:	25-2.7k Hz
Voice Coil Diameter	音圈直径:	115mm/4.5 inch
Winding Material	线材:	Copper
Magnet	磁体:	Neodymium Ring

**MR21N10C-A**

Nominal Diameter	标准直径:	550mm/21inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	2000W (AES)
Maximum Power	最大功率:	4000W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	29-1.5k Hz
Voice Coil Diameter	音圈直径:	152mm/6inch
Winding Material	线材:	Copper
Magnet	磁体:	Neodymium Ring

**MR21SW001A-01**

Nominal Diameter	标准直径:	550mm/21inch
Nominal Impedance	标称阻抗:	2Ω
AES Power Handling	AES功率:	1800W (AES)
Maximum Power	最大功率:	3600W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	30-1.8k Hz
Voice Coil Diameter	音圈直径:	152mm/6 inch
Winding Material	线材:	Copper
Magnet	磁体:	Neodymium Ring



MR04F17C

Nominal Diameter	标准直径 :	116mm/4inch
Nominal Impedance	标称阻抗 :	4Ω
AES Power Handling	AES功率 :	40W (AES)
Maximum Power	最大功率 :	80W
Sensitivity 1W/1M	灵敏度 :	90dB
Frequency Range	频响范围 :	95-7.2k Hz
Voice Coil Diameter	音圈直径 :	25mm/1 inch
Winding Material	线 材 :	Copper
Magnet	磁 体 :	Φ80Ferrite Ring/H20mm



MR05F16C

Nominal Diameter	标准直径 :	148mm/5inch
Nominal Impedance	标称阻抗 :	4Ω
AES Power Handling	AES功率 :	60W (AES)
Maximum Power	最大功率 :	120W
Sensitivity 1W/1M	灵敏度 :	92dB
Frequency Range	频响范围 :	68-13k Hz
Voice Coil Diameter	音圈直径 :	25mm/1 inch
Winding Material	线 材 :	Copper
Magnet	磁 体 :	Φ90Ferrite Ring/H18mm



MR06F65C

Nominal Diameter	标准直径 :	177mm/6.5inch
Nominal Impedance	标称阻抗 :	4Ω
AES Power Handling	AES功率 :	70W (AES)
Maximum Power	最大功率 :	140W
Sensitivity 1W/1M	灵敏度 :	93dB
Frequency Range	频响范围 :	59-8k HZ
Voice Coil Diameter	音圈直径 :	25mm/1 inch
Winding Material	线 材 :	Copper
Magnet	磁 体 :	Φ100Ferrite Ring/H20mm



MR05F25C

Nominal Diameter	标准直径 :	133mm/5.25inch
Nominal Impedance	标称阻抗 :	16Ω
AES Power Handling	AES功率 :	50W (AES)
Maximum Power	最大功率 :	100W
Sensitivity 1W/1M	灵敏度 :	93dB
Frequency Range	频响范围 :	102-15k Hz
Voice Coil Diameter	音圈直径 :	25.5mm/1.2inch
Winding Material	线 材 :	Aluminium
Magnet	磁 体 :	Φ90Ferrite Ring/H18mm



MR05F25D-M

Nominal Diameter	标准直径 :	133mm/5inch
Nominal Impedance	标称阻抗 :	4Ω
AES Power Handling	AES功率 :	40W (AES)
Maximum Power	最大功率 :	80W
Sensitivity 1W/1M	灵敏度 :	92dB
Frequency Range	频响范围 :	500-12k Hz
Voice Coil Diameter	音圈直径 :	25mm/1inch
Winding Material	线 材 :	Aluminium
Magnet	磁 体 :	Φ80Ferrite Ring/H15mm



MR05F13C-D

Nominal Diameter	标准直径 :	133mm/5inch
Nominal Impedance	标称阻抗 :	4Ω
AES Power Handling	AES功率 :	50W (AES)
Maximum Power	最大功率 :	100W
Sensitivity 1W/1M	灵敏度 :	91dB
Frequency Range	频响范围 :	115-13k Hz
Voice Coil Diameter	音圈直径 :	25mm/1 inch
Winding Material	线 材 :	Aluminium
Magnet	磁 体 :	Φ90Ferrite Ring/H18mm



MR05N20C-A

Nominal Diameter	标准直径 :	133mm/5.25inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	50W (AES)
Maximum Power	最大功率 :	100W
Sensitivity 1W/1M	灵敏度 :	93dB
Frequency Range	频响范围 :	103-15k Hz
Voice Coil Diameter	音圈直径 :	25mm/1inch
Winding Material	线 材 :	Aluminium
Magnet	磁 体 :	Neodymium Ring



MR06F45C

Nominal Diameter	标准直径 :	167mm/6.5 inch
Nominal Impedance	标称阻抗 :	4Ω
AES Power Handling	AES功率 :	80W (AES)
Maximum Power	最大功率 :	160W
Sensitivity 1W/1M	灵敏度 :	91dB
Frequency Range	频响范围 :	64-6.7k Hz
Voice Coil Diameter	音圈直径 :	35mm/1.4 inch
Winding Material	线 材 :	Copper
Magnet	磁 体 :	Φ100Ferrite Ring/H20mm



MR06F88C

Nominal Diameter	标准直径 :	182mm/6.5inch
Nominal Impedance	标称阻抗 :	4Ω
AES Power Handling	AES功率 :	60W (AES)
Maximum Power	最大功率 :	120W
Sensitivity 1W/1M	灵敏度 :	90dB
Frequency Range	频响范围 :	50.4-10k Hz
Voice Coil Diameter	音圈直径 :	30mm/1.1 inch
Winding Material	线 材 :	Aluminium
Magnet	磁 体 :	Φ110Ferrite Ring/H20



MR06F06D

Nominal Diameter	标准直径 :	167mm/6.5 inch
Nominal Impedance	标称阻抗 :	4Ω
AES Power Handling	AES功率 :	80W (AES)
Maximum Power	最大功率 :	160W
Sensitivity 1W/1M	灵敏度 :	91dB
Frequency Range	频响范围 :	56-8k Hz
Voice Coil Diameter	音圈直径 :	35mm/1.4 inch
Winding Material	线 材 :	Aluminium
Magnet	磁 体 :	Φ100Ferrite Ring/H20mm



MR06F52C

Nominal Diameter	标准直径 :	167mm/6.5inch
Nominal Impedance	标称阻抗 :	2Ω
AES Power Handling	AES功率 :	60W (AES)
Maximum Power	最大功率 :	120W
Sensitivity 1W/1M	灵敏度 :	91dB
Frequency Range	频响范围 :	41-2.7k Hz
Voice Coil Diameter	音圈直径 :	30mm/1.2 inch
Winding Material	线 材 :	Copper
Magnet	磁 体 :	Φ110Ferrite Ring/H20mm



MR06F53C

Nominal Diameter	标准直径 :	167mm/6.5inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	80W (AES)
Maximum Power	最大功率 :	160W
Sensitivity 1W/1M	灵敏度 :	91dB
Frequency Range	频响范围 :	115-10.2k Hz
Voice Coil Diameter	音圈直径 :	38mm/1.5 inch
Winding Material	线 材 :	Copper
Magnet	磁 体 :	Φ115Ferrite Ring/H15mm



MR06F25D-M

Nominal Diameter	标准直径:	167mm/6.5inch
Nominal Impedance	标称阻抗:	4Ω
AES Power Handling	AES功率:	50W (AES)
Maximum Power	最大功率:	100W
Sensitivity 1W/1M	灵敏度:	94dB
Frequency Range	频响范围:	450-9.5k Hz
Voice Coil Diameter	音圈直径:	25mm/1inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Φ80Ferrite Ring/H15mm



MR06F35D-M

Nominal Diameter	标准直径:	167mm/6.5inch
Nominal Impedance	标称阻抗:	4Ω
AES Power Handling	AES功率:	80W (AES)
Maximum Power	最大功率:	160W
Sensitivity 1W/1M	灵敏度:	95dB
Frequency Range	频响范围:	380-5.5k Hz
Voice Coil Diameter	音圈直径:	35mm/1.4inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Φ100Ferrite Ring/H20mm



MR06F19D-M

Nominal Diameter	标准直径:	167mm/6.5inch
Nominal Impedance	标称阻抗:	4Ω
AES Power Handling	AES功率:	150W (AES)
Maximum Power	最大功率:	300W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	450-12k Hz
Voice Coil Diameter	音圈直径:	38.5mm/1.4inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Φ135Ferrite Ring/H20mm



MR08F01D

Nominal Diameter	标准直径:	217mm/8inch
Nominal Impedance	标称阻抗:	4Ω
AES Power Handling	AES功率:	60W (AES)
Maximum Power	最大功率:	120W
Sensitivity 1W/1M	灵敏度:	94dB
Frequency Range	频响范围:	64-6.5k Hz
Voice Coil Diameter	音圈直径:	35mm/1.4 inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ110Ferrite Ring/H20mm



MR08F92C

Nominal Diameter	标准直径:	217mm/8inch
Nominal Impedance	标称阻抗:	4Ω
AES Power Handling	AES功率:	60W (AES)
Maximum Power	最大功率:	120W
Sensitivity 1W/1M	灵敏度:	93dB
Frequency Range	频响范围:	52-8k Hz
Voice Coil Diameter	音圈直径:	35mm/1.4 inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ110Ferrite Ring/H20mm



MR08H25A

Nominal Diameter	标准直径:	210mm/8 inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	150W (AES)
Maximum Power	最大功率:	300W
Sensitivity 1W/1M	灵敏度:	93dB
Frequency Range	频响范围:	50-5.4k Hz
Voice Coil Diameter	音圈直径:	50mm/2 inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ120Ferrite Ring/H20mm



MR08F68D-16

Nominal Diameter	标准直径:	210mm / 8inch
Nominal Impedance	标称阻抗:	16Ω
AES Power Handling	AES功率:	200W (AES)
Maximum Power	最大功率:	400W
Sensitivity 1W/1M	灵敏度:	97 dB
Frequency Range	频响范围:	90-5.5k Hz
Voice Coil Diameter	音圈直径:	50mm / 2inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ135Ferrite Ring/H20mm



MR08F72C

Nominal Diameter	标准直径:	210mm/8 inch
Nominal Impedance	标称阻抗:	4Ω
AES Power Handling	AES功率:	100W (AES)
Maximum Power	最大功率:	200W
Sensitivity 1W/1M	灵敏度:	95dB
Frequency Range	频响范围:	89-11.5k Hz
Voice Coil Diameter	音圈直径:	38mm/1.5 inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Φ140Ferrite Ring/H20mm



MR10F72C

Nominal Diameter	标准直径:	250mm/10inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	120W (AES)
Maximum Power	最大功率:	240W
Sensitivity 1W/1M	灵敏度:	93dB
Frequency Range	频响范围:	40-4.9k Hz
Voice Coil Diameter	音圈直径:	35mm/1.4inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ100Ferrite Ring/H20/18mm



MR10H22

Nominal Diameter	标准直径:	260mm/10 inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	200W
Maximum Power	最大功率:	400W
Sensitivity 1W/1M	灵敏度:	93dB
Frequency Range	频响范围:	33-3.2k Hz
Voice Coil Diameter	音圈直径:	50mm/2 inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ120Ferrite Ring/H20/15mm



MR10F60D

Nominal Diameter	标准直径:	257mm/10inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	150W (AES)
Maximum Power	最大功率:	300W
Sensitivity 1W/1M	灵敏度:	94dB
Frequency Range	频响范围:	54-5k Hz
Voice Coil Diameter	音圈直径:	50mm/2inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ120Ferrite Ring/H20mm



MR10F96C

Nominal Diameter	标准直径:	261mm/ 10 inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	250W
Maximum Power	最大功率:	500W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	53-4.8k Hz
Voice Coil Diameter	音圈直径:	65mm/2.5inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ156Ferrite Ring/H20mm



MR10F67C

Nominal Diameter	标准直径 :	257mm/10inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	200W (AES)
Maximum Power	最大功率 :	400W
Sensitivity 1W/1M	灵敏度 :	92dB
Frequency Range	频响范围 :	36-2.3k Hz
Voice Coil Diameter	音圈直径 :	50mm/2 inch
Winding Material	线 材 :	Copper
Magnet	磁 体 :	Φ140Ferrite Ring/H20mm



MR10F83D-A

Nominal Diameter	标准直径 :	260mm/10inch
Nominal Impedance	标称阻抗 :	4Ω
AES Power Handling	AES功率 :	250W (AES)
Maximum Power	最大功率 :	500W
Sensitivity 1W/1M	灵敏度 :	94dB
Frequency Range	频响范围 :	51-4.5k Hz
Voice Coil Diameter	音圈直径 :	65mm/2.5inch
Winding Material	线 材 :	Copper
Magnet	磁 体 :	Φ156Ferrite Ring/H20mm



MR10H35B-01

Nominal Diameter	标准直径 :	257mm/10inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	250W (AES)
Maximum Power	最大功率 :	500W
Sensitivity 1W/1M	灵敏度 :	95dB
Frequency Range	频响范围 :	55-6k Hz
Voice Coil Diameter	音圈直径 :	65mm/2.5 inch
Winding Material	线 材 :	Copper
Magnet	磁 体 :	Φ156Ferrite Ring/H20mm



MR10F68E

Nominal Diameter	标准直径 :	257mm/10inch
Nominal Impedance	标称阻抗 :	4Ωx2
AES Power Handling	AES功率 :	100Wx2
Maximum Power	最大功率 :	200Wx2
Sensitivity 1W/1M	灵敏度 :	95dB
Frequency Range	频响范围 :	50-4k Hz
Voice Coil Diameter	音圈直径 :	50mm/2 inch
Winding Material	线 材 :	Copper
Magnet	磁 体 :	Φ140Ferrite Ring/H20mm



MR12F56D

Nominal Diameter	标准直径 :	305mm/12inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	120W (AES)
Maximum Power	最大功率 :	240W
Sensitivity 1W/1M	灵敏度 :	93dB
Frequency Range	频响范围 :	50-5.5k Hz
Voice Coil Diameter	音圈直径 :	35mm/1.5inch
Winding Material	线 材 :	Copper
Magnet	磁 体 :	Φ120Ferrite Ring/H20mm



MR12F07E-B

Nominal Diameter	标准直径 :	305mm/12inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	150W (AES)
Maximum Power	最大功率 :	300W
Sensitivity 1W/1M	灵敏度 :	94dB
Frequency Range	频响范围 :	42-5k Hz
Voice Coil Diameter	音圈直径 :	50mm/2 inch
Winding Material	线 材 :	Copper
Magnet	磁 体 :	Φ140Ferrite Ring/H20mm



MR12F82D-A

Nominal Diameter	标准直径 :	305mm/12inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	250W (AES)
Maximum Power	最大功率 :	500W
Sensitivity 1W/1M	灵敏度 :	94dB
Frequency Range	频响范围 :	45-4.5k Hz
Voice Coil Diameter	音圈直径 :	65mm/2.5inch
Winding Material	线 材 :	Copper
Magnet	磁 体 :	Φ156Ferrite Ring/H20mm



MR12H116-A

Nominal Diameter	标准直径 :	310mm/12 inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	300W
Maximum Power	最大功率 :	600W
Sensitivity 1W/1M	灵敏度 :	94dB
Frequency Range	频响范围 :	55-4.1k Hz
Voice Coil Diameter	音圈直径 :	75mm/3 inch
Winding Material	线 材 :	Copper
Magnet	磁 体 :	Φ170Ferrite Ring/H20mm



MR12F68E

Nominal Diameter	标准直径 :	305mm/12inch
Nominal Impedance	标称阻抗 :	4Ωx2
AES Power Handling	AES功率 :	100Wx2
Maximum Power	最大功率 :	200Wx2
Sensitivity 1W/1M	灵敏度 :	95dB
Frequency Range	频响范围 :	50-4k Hz
Voice Coil Diameter	音圈直径 :	50mm/2inch
Winding Material	线 材 :	Copper
Magnet	磁 体 :	Φ140Ferrite Ring/H20mm



MR15F37D-A

Nominal Diameter	标准直径 :	383mm/15inch
Nominal Impedance	标称阻抗 :	4Ω
AES Power Handling	AES功率 :	200W (AES)
Maximum Power	最大功率 :	400W
Sensitivity 1W/1M	灵敏度 :	93dB
Frequency Range	频响范围 :	48-5.5k Hz
Voice Coil Diameter	音圈直径 :	50mm/2 inch
Winding Material	线 材 :	Copper
Magnet	磁 体 :	Φ140Ferrite Ring/H20mm



MR15F32C-A

Nominal Diameter	标准直径 :	383mm/15inch
Nominal Impedance	标称阻抗 :	8Ω
AES Power Handling	AES功率 :	250W (AES)
Maximum Power	最大功率 :	500W
Sensitivity 1W/1M	灵敏度 :	94dB
Frequency Range	频响范围 :	38.3-3.1k Hz
Voice Coil Diameter	音圈直径 :	65mm/2.5 inch
Winding Material	线 材 :	Copper
Magnet	磁 体 :	Φ156Ferrite Ring/H20mm



MR15F68E

Nominal Diameter	标准直径 :	383mm/15inch
Nominal Impedance	标称阻抗 :	4Ωx2
AES Power Handling	AES功率 :	150Wx2
Maximum Power	最大功率 :	300Wx2
Sensitivity 1W/1M	灵敏度 :	96dB
Frequency Range	频响范围 :	32-3k Hz
Voice Coil Diameter	音圈直径 :	50mm/2inch
Winding Material	线 材 :	Copper
Magnet	磁 体 :	Φ140Ferrite Ring/H20mm



MR15F14A-A

Nominal Diameter	标准直径:	385mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	300W (AES)
Maximum Power	最大功率:	600W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	41-3.9k Hz
Voice Coil Diameter	音圈直径:	75mm/3 inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ170Ferrite Ring/H20mm



MR15F96D

Nominal Diameter	标准直径:	385mm/15inch
Nominal Impedance	标称阻抗:	4Ω
AES Power Handling	AES功率:	300W (AES)
Maximum Power	最大功率:	600W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	50-4k Hz
Voice Coil Diameter	音圈直径:	75mm/3inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ170Ferrite Ring/H20mm



MR15F95D

Nominal Diameter	标准直径:	385mm/15inch
Nominal Impedance	标称阻抗:	4Ω
AES Power Handling	AES功率:	350W (AES)
Maximum Power	最大功率:	700W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	51-4k Hz
Voice Coil Diameter	音圈直径:	75mm/3inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ190Ferrite Ring/H20mm



MR15F64C

Nominal Diameter	标准直径:	385mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	300W (AES)
Maximum Power	最大功率:	600W
Sensitivity 1W/1M	灵敏度:	95dB
Frequency Range	频响范围:	36-5.4k Hz
Voice Coil Diameter	音圈直径:	75mm/3 inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ170Ferrite Ring/H20mm



MR15F63C

Nominal Diameter	标准直径:	385mm/15inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	300W (AES)
Maximum Power	最大功率:	600W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	35-5.3k Hz
Voice Coil Diameter	音圈直径:	75mm/3 inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ190Ferrite Ring/H20mm



MR15N15D

Nominal Diameter	标准直径:	385mm/15inch
Nominal Impedance	标称阻抗:	4Ω
AES Power Handling	AES功率:	350W (AES)
Maximum Power	最大功率:	700W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	40-3.5k Hz
Voice Coil Diameter	音圈直径:	75mm/3 inch
Winding Material	线材:	Copper
Magnet	磁体:	Neodymium Ring



MR18F64C-D

Nominal Diameter	标准直径:	460mm/18inch
Nominal Impedance	标称阻抗:	4Ω
AES Power Handling	AES功率:	450W (AES)
Maximum Power	最大功率:	900W
Sensitivity 1W/1M	灵敏度:	95dB
Frequency Range	频响范围:	36-2k Hz
Voice Coil Diameter	音圈直径:	75mm/3inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ190Ferrite Ring/H20mm



MR18F71C-4

Nominal Diameter	标准直径:	460mm/18inch
Nominal Impedance	标称阻抗:	4Ω
AES Power Handling	AES功率:	300W (AES)
Maximum Power	最大功率:	600W
Sensitivity 1W/1M	灵敏度:	95dB
Frequency Range	频响范围:	30-4k Hz
Voice Coil Diameter	音圈直径:	65mm/2.5inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ156Ferrite Ring/H20mm



MR18F68E

Nominal Diameter	标准直径:	460mm /18 inch
Nominal Impedance	标称阻抗:	4Ω+4Ω
AES Power Handling	AES功率:	250W (AES)
Maximum Power	最大功率:	500W
Sensitivity 1W/1M	灵敏度:	95dB
Frequency Range	频响范围:	34-3k Hz
Voice Coil Diameter	音圈直径:	65mm/2.5inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ156Ferrite Ring/H20mm



MR18F22D-4

Nominal Diameter	标准直径:	462mm/18inch
Nominal Impedance	标称阻抗:	4Ω
AES Power Handling	AES功率:	350W (AES)
Maximum Power	最大功率:	700W
Sensitivity 1W/1M	灵敏度:	94dB
Frequency Range	频响范围:	35-4k Hz
Voice Coil Diameter	音圈直径:	75mm/3inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ170Ferrite Ring/H20mm



MR18F72C

Nominal Diameter	标准直径:	462mm/18inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	400W (AES)
Maximum Power	最大功率:	800W
Sensitivity 1W/1M	灵敏度:	95dB
Frequency Range	频响范围:	30-6.3k Hz
Voice Coil Diameter	音圈直径:	75mm/3 inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ190Ferrite Ring/H20mm



MR18F01D

Nominal Diameter	标准直径:	462mm/18inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	500W (AES)
Maximum Power	最大功率:	1000W
Sensitivity 1W/1M	灵敏度:	95dB
Frequency Range	频响范围:	40-3k Hz
Voice Coil Diameter	音圈直径:	100mm/4 inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ220Ferrite Ring/H20mm



MR05H15-34T

Nominal Diameter	标准直径:	135/5.25inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	100W (AES)
Maximum Power	最大功率:	200W
Sensitivity 1W/1M	灵敏度:	92dB
Frequency Range	频响范围:	95-18k Hz
Voice Coil Diameter	音圈直径:	38mm/1.5 inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Φ115Ferrite Ring/H20mm



MR06H17-34T

Nominal Diameter	标准直径:	175mm/6inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	150W (AES)
Maximum Power	最大功率:	300W
Sensitivity 1W/1M	灵敏度:	95dB
Frequency Range	频响范围:	80-18k Hz
Voice Coil Diameter	音圈直径:	50mm/2inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ120Ferrite Ring/H20mm



MR06H17-25T

Nominal Diameter	标准直径:	162mm/6.5 inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	150W (AES)
Maximum Power	最大功率:	300W
Sensitivity 1W/1M	灵敏度:	95dB
Frequency Range	频响范围:	80-18k Hz
Voice Coil Diameter	音圈直径:	50mm/2 inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Φ120Ferrite Ring/H20mm



MR06H18-25T

Nominal Diameter	标准直径:	162mm /6.5inch
Nominal Impedance	标称阻抗:	4Ω
AES Power Handling	AES功率:	100W (AES)
Maximum Power	最大功率:	200W
Sensitivity 1W/1M	灵敏度:	94dB
Frequency Range	频响范围:	50-20k Hz
Voice Coil Diameter	音圈直径:	35mm / 1.4 inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ120Ferrite Ring/H20mm



MR08H15-34T-A

Nominal Diameter	标准直径:	200mm/8inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	150W (AES)
Maximum Power	最大功率:	300W
Sensitivity 1W/1M	灵敏度:	95dB
Frequency Range	频响范围:	75-18k Hz
Voice Coil Diameter	音圈直径:	50mm/2 inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Φ135Ferrite Ring/H20mm



MR08H17-34T

Nominal Diameter	标准直径:	200mm/8inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	150W (AES)
Maximum Power	最大功率:	300W
Sensitivity 1W/1M	灵敏度:	95dB
Frequency Range	频响范围:	70-18k Hz
Voice Coil Diameter	音圈直径:	50mm/2inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ135Ferrite Ring/H20mm



MR10H17-44T

Nominal Diameter	标准直径:	260mm/10 inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	250W (AES)
Maximum Power	最大功率:	500W
Sensitivity 1W/1M	灵敏度:	95dB
Frequency Range	频响范围:	68-20k Hz
Voice Coil Diameter	音圈直径:	65mm/2.5 inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Φ156Ferrite Ring/H20mm



MR12H13-44T

Nominal Diameter	标准直径:	312mm/12 inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	300W (AES)
Maximum Power	最大功率:	600W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	60-18k Hz
Voice Coil Diameter	音圈直径:	75mm/3 inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ180Ferrite Ring/H20mm



MR12H17-75T

Nominal Diameter	标准直径:	312mm/12 inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	350W (AES)
Maximum Power	最大功率:	700W
Sensitivity 1W/1M	灵敏度:	96dB
Frequency Range	频响范围:	55-20k Hz
Voice Coil Diameter	音圈直径:	75mm/3 inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Φ190Ferrite Ring/H20mm



MR15H17-75T

Nominal Diameter	标准直径:	395mm/15 inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	400W (AES)
Maximum Power	最大功率:	800W
Sensitivity 1W/1M	灵敏度:	97dB
Frequency Range	频响范围:	49-20k Hz
Voice Coil Diameter	音圈直径:	75mm/3 inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Φ190Ferrite Ring/H20mm



MR12N76-75T

Nominal Diameter	标准直径:	315mm/12 inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	400W (AES)
Maximum Power	最大功率:	800W
Sensitivity 1W/1M	灵敏度:	98dB
Frequency Range	频响范围:	58-18k Hz
Voice Coil Diameter	音圈直径:	75mm/3 inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Neodymium Ring



MR15N76-75T

Nominal Diameter	标准直径:	380mm/15 inch
Nominal Impedance	标称阻抗:	8Ω
AES Power Handling	AES功率:	450W
Maximum Power	最大功率:	900W
Sensitivity 1W/1M	灵敏度:	98dB
Frequency Range	频响范围:	49.5-18k Hz
Voice Coil Diameter	音圈直径:	75mm/3inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Neodymium Ring



MR4001

Nominal Diameter	标准直径:	104mm/4inch
Nominal Impedance	标称阻抗:	4Ω
AES Power Handling	AES功率:	40W (AES)
Maximum Power	最大功率:	80W
Sensitivity 1W/1M	灵敏度:	88dB
Frequency Range	频响范围:	100-20k Hz
Voice Coil Diameter	音圈直径:	25mm/1inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ80Ferrite Ring/H15mm



MR5001

Nominal Diameter	标准直径:	130mm/5 inch
Nominal Impedance	标称阻抗:	4Ω
AES Power Handling	AES功率:	50W
Maximum Power	最大功率:	100W
Sensitivity 1W/1M	灵敏度:	88dB
Frequency Range	频响范围:	70~20k Hz
Voice Coil Diameter	音圈直径:	25mm/1 inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ80Ferrite Ring/H15mm



MR6501

Nominal Diameter	标准直径:	165mm/6.46inch
Nominal Impedance	标称阻抗:	4Ω
AES Power Handling	AES功率:	50W (AES)
Maximum Power	最大功率:	100W
Sensitivity 1W/1M	灵敏度:	91dB
Frequency Range	频响范围:	58-20k Hz
Voice Coil Diameter	音圈直径:	25mm/1 inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ80Ferrite Ring/H15mm



MR6901

Nominal Diameter	标准直径:	165mm/6.5inch
Nominal Impedance	标称阻抗:	4Ω
AES Power Handling	AES功率:	80W (AES)
Maximum Power	最大功率:	160W
Sensitivity 1W/1M	灵敏度:	92dB
Frequency Range	频响范围:	2.7-20k Hz
Voice Coil Diameter	音圈直径:	25mm/1 inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ100Ferrite Ring/H20mm



MR4106

Nominal Diameter	标准直径:	105mm/4inch
Nominal Impedance	标称阻抗:	4Ω
AES Power Handling	AES功率:	40W (AES)
Maximum Power	最大功率:	80W
Sensitivity 1W/1M	灵敏度:	88dB
Frequency Range	频响范围:	251-18k Hz
Voice Coil Diameter	音圈直径:	25mm/1inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Φ80Ferrite Ring/H15mm



MR0610B

Nominal Diameter	标准直径:	167mm/6inch
Nominal Impedance	标称阻抗:	4Ω
AES Power Handling	AES功率:	50W (AES)
Maximum Power	最大功率:	100W
Sensitivity 1W/1M	灵敏度:	91dB
Frequency Range	频响范围:	111-15k Hz
Voice Coil Diameter	音圈直径:	25mm/1inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Φ80Ferrite Ring/H15mm



MR5106

Nominal Diameter	标准直径:	130mm/5inch
Nominal Impedance	标称阻抗:	4Ω
AES Power Handling	AES功率:	50W (AES)
Maximum Power	最大功率:	100W
Sensitivity 1W/1M	灵敏度:	89dB
Frequency Range	频响范围:	180-18k Hz
Voice Coil Diameter	音圈直径:	25mm/1inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Φ80Ferrite Ring/H15mm



MR8106

Nominal Diameter	标准直径:	210mm/8inch
Nominal Impedance	标称阻抗:	4Ω
AES Power Handling	AES功率:	80W (AES)
Maximum Power	最大功率:	160W
Sensitivity 1W/1M	灵敏度:	91dB
Frequency Range	频响范围:	81-13k Hz
Voice Coil Diameter	音圈直径:	30.5mm/1.4inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Φ115Ferrite Ring/H15mm



MR06F09D-A

Nominal Diameter	标准直径:	167mm/6inch
Nominal Impedance	标称阻抗:	4Ω
AES Power Handling	AES功率:	100W (AES)
Maximum Power	最大功率:	200W
Sensitivity 1W/1M	灵敏度:	93dB
Frequency Range	频响范围:	122-15k Hz
Voice Coil Diameter	音圈直径:	38mm/1.5inch
Winding Material	线材:	Aluminium
Magnet	磁体:	Φ120Ferrite Ring/H20mm



MR08F01G

Nominal Diameter	标准直径:	210mm/8inch
Nominal Impedance	标称阻抗:	4Ω
AES Power Handling	AES功率:	150W (AES)
Maximum Power	最大功率:	300W
Sensitivity 1W/1M	灵敏度:	92dB
Frequency Range	频响范围:	47-3k Hz
Voice Coil Diameter	音圈直径:	50mm/2inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ126Ferrite Ring/H20*2mm



MR10F01G

Nominal Diameter	标准直径:	257mm/10inch
Nominal Impedance	标称阻抗:	4Ω
AES Power Handling	AES功率:	300W (AES)
Maximum Power	最大功率:	600W
Sensitivity 1W/1M	灵敏度:	95dB
Frequency Range	频响范围:	47-2k Hz
Voice Coil Diameter	音圈直径:	50mm/2inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ142Ferrite Ring/H20*2mm



MR10F02G

Nominal Diameter	标准直径:	278mm/10inch
Nominal Impedance	标称阻抗:	4Ω
AES Power Handling	AES功率:	450W (AES)
Maximum Power	最大功率:	900W
Sensitivity 1W/1M	灵敏度:	95dB
Frequency Range	频响范围:	49-2k Hz
Voice Coil Diameter	音圈直径:	65mm/2.5inch
Winding Material	线材:	Copper
Magnet	磁体:	Φ156Ferrite Ring/H20*2mm



MR10H01G

Nominal Diameter	标准直径 :	280mm/10inch
Nominal Impedance	标称阻抗 :	4Ωx2
AES Power Handling	AES功率 :	500W (AES)
Maximum Power	最大功率 :	1000W
Sensitivity 1W/1M	灵敏度 :	96dB
Frequency Range	频响范围 :	53-2k Hz
Voice Coil Diameter	音圈直径 :	65mm/2.5inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ156Ferrite Ring/H20*2mm



MR10HS01G

Nominal Diameter	标准直径 :	265mm /10inch
Nominal Impedance	标称阻抗 :	4Ωx2
AES Power Handling	AES功率 :	800W (AES)
Maximum Power	最大功率 :	1600W
Sensitivity 1W/1M	灵敏度 :	95dB
Frequency Range	频响范围 :	38-2k Hz
Voice Coil Diameter	音圈直径 :	75mm / 3 inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ190*3Ferrite Ring/H20*3mm



MR12HS01G

Nominal Diameter	标准直径 :	320mm / 12inch
Nominal Impedance	标称阻抗 :	4Ωx2
AES Power Handling	AES功率 :	1000W (AES)
Maximum Power	最大功率 :	2000W
Sensitivity 1W/1M	灵敏度 :	95dB
Frequency Range	频响范围 :	37-1.8k Hz
Voice Coil Diameter	音圈直径 :	75mm / 3 inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ220*3Ferrite Ring/H20*3mm



MR12F01G

Nominal Diameter	标准直径 :	312mm/12inch
Nominal Impedance	标称阻抗 :	4Ω
AES Power Handling	AES功率 :	350W (AES)
Maximum Power	最大功率 :	700W
Sensitivity 1W/1M	灵敏度 :	95dB
Frequency Range	频响范围 :	39-1.8k Hz
Voice Coil Diameter	音圈直径 :	50mm/2inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ156Ferrite Ring/H20*2mm



MR12F02G

Nominal Diameter	标准直径 :	325mm/12inch
Nominal Impedance	标称阻抗 :	4Ω
AES Power Handling	AES功率 :	500W (AES)
Maximum Power	最大功率 :	1000W
Sensitivity 1W/1M	灵敏度 :	95dB
Frequency Range	频响范围 :	39-1.5k Hz
Voice Coil Diameter	音圈直径 :	75mm/3inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ156Ferrite Ring/H20*2mm



MR12F03G

Nominal Diameter	标准直径 :	312mm/12 inch
Nominal Impedance	标称阻抗 :	4Ω
AES Power Handling	AES功率 :	350W
Maximum Power	最大功率 :	700W
Sensitivity 1W/1M	灵敏度 :	95dB
Frequency Range	频响范围 :	45-1.8k Hz
Voice Coil Diameter	音圈直径 :	50mm/2 inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ140Ferrite Ring/H20*2mm



MR12H01G

Nominal Diameter	标准直径 :	325mm/12inch
Nominal Impedance	标称阻抗 :	4Ωx2
AES Power Handling	AES功率 :	700W (AES)
Maximum Power	最大功率 :	1400W
Sensitivity 1W/1M	灵敏度 :	96dB
Frequency Range	频响范围 :	37-1.5k Hz
Voice Coil Diameter	音圈直径 :	75mm/3inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ180Ferrite Ring/H20*2mm



MR12H02G

Nominal Diameter	标准直径 :	325mm/12inch
Nominal Impedance	标称阻抗 :	4Ωx2
AES Power Handling	AES功率 :	900W (AES)
Maximum Power	最大功率 :	1800W
Sensitivity 1W/1M	灵敏度 :	96dB
Frequency Range	频响范围 :	43-1.2k Hz
Voice Coil Diameter	音圈直径 :	75mm/3inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ220*2Ferrite Ring/H20*2mm



MR12HS01-A

Nominal Diameter	标准直径 :	320mm /12inch
Nominal Impedance	标称阻抗 :	4Ωx2
AES Power Handling	AES功率 :	1000W (AES)
Maximum Power	最大功率 :	2000W
Sensitivity 1W/1M	灵敏度 :	95dB
Frequency Range	频响范围 :	37-1.8k Hz
Voice Coil Diameter	音圈直径 :	75mm /3inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ220*3Ferrite Ring/H20*3mm



MR12H92E

Nominal Diameter	标准直径 :	320mm/12inch
Nominal Impedance	标称阻抗 :	4Ωx2
AES Power Handling	AES功率 :	600W (AES)
Maximum Power	最大功率 :	1200W
Sensitivity 1W/1M	灵敏度 :	90dB
Frequency Range	频响范围 :	62-3k Hz
Voice Coil Diameter	音圈直径 :	50mm/2inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ156Ferrite Ring/H25*2mm



MR12HS02G

Nominal Diameter	标准直径 :	312mm/12inch
Nominal Impedance	标称阻抗 :	4Ωx2
AES Power Handling	AES功率 :	1000W (AES)
Maximum Power	最大功率 :	2000W
Sensitivity 1W/1M	灵敏度 :	96dB
Frequency Range	频响范围 :	35-1.2k Hz
Voice Coil Diameter	音圈直径 :	100mm/4inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ220*3Ferrite Ring/H20*3mm



MR15HS02G

Nominal Diameter	标准直径 :	390mm/15inch
Nominal Impedance	标称阻抗 :	4Ωx2
AES Power Handling	AES功率 :	1100W (AES)
Maximum Power	最大功率 :	2200W
Sensitivity 1W/1M	灵敏度 :	96dB
Frequency Range	频响范围 :	32-1k Hz
Voice Coil Diameter	音圈直径 :	100mm/4inch
Winding Material	线材 :	Copper
Magnet	磁体 :	Φ220*3Ferrite Ring/H20*3mm



MR80-3

Throat Diameter	喉口直径 :	27mm/1.1 inch
Nominal Impedance	标称阻抗 :	8Ω
RMS Power Input	额定功率 :	30W
MAX Power Input	最大功率 :	60W
Sensitivity 1W/1M	灵敏度 :	103dB
Frequency Range	频响范围 :	1.3K~15k Hz
Voice Coil Diameter	音圈直径 :	25mm/1inch
Diaphragm Material	膜片材质 :	resinous
Magnet	磁体 :	Φ80Ferrite Ring/H15mm



MR250A

Throat Diameter	喉口直径 :	59mm/2.3inch
Nominal Impedance	标称阻抗 :	4Ω
RMS Power Input	额定功率 :	35W
MAX Power Input	最大功率 :	45W
Sensitivity 1W/1M	灵敏度 :	100dB
Frequency Range	频响范围 :	2~20k Hz
Voice Coil Diameter	音圈直径 :	25mm/1inch
Diaphragm Material	膜片材质 :	Aluminum
Magnet	磁体 :	Φ70Ferrite Ring/H10mm



MR340L2

Throat Diameter	喉口直径 :	25mm/1inch
Nominal Impedance	标称阻抗 :	8Ω
RMS Power Input	额定功率 :	60W
MAX Power Input	最大功率 :	120W
Sensitivity 1W/1M	灵敏度 :	103dB
Frequency Range	频响范围 :	800~20k Hz
Voice Coil Diameter	音圈直径 :	34mm/1.4inch
Diaphragm Material	膜片材质 :	Pek
Magnet	磁体 :	Φ90Ferrite Ring/H15mm



MR340L

Throat Diameter	喉口直径 :	25mm/1inch
Nominal Impedance	标称阻抗 :	8Ω
RMS Power Input	额定功率 :	30W
MAX Power Input	最大功率 :	60W
Sensitivity 1W/1M	灵敏度 :	103dB
Frequency Range	频响范围 :	1~20k Hz
Voice Coil Diameter	音圈直径 :	34mm/1.4inch
Diaphragm Material	膜片材质 :	Titanium
Magnet	磁体 :	Φ90Ferrite Ring/H15mm



MR44-23

Throat Diameter	喉口直径 :	25mm/1 inch
Nominal Impedance	标称阻抗 :	8Ω
RMS Power Input	额定功率 :	60W
MAX Power Input	最大功率 :	120W
Sensitivity 1W/1M	灵敏度 :	104dB
Frequency Range	频响范围 :	1~20k Hz
Voice Coil Diameter	音圈直径 :	44mm/1.7inch
Diaphragm Material	膜片材质 :	Titanium
Magnet	磁体 :	Φ115Ferrite Ring/H15mm



MR4408LJ

Throat Diameter	喉口直径 :	25mm/1inch
Nominal Impedance	标称阻抗 :	8Ω
RMS Power Input	额定功率 :	60W
MAX Power Input	最大功率 :	120W
Sensitivity 1W/1M	灵敏度 :	106dB
Frequency Range	频响范围 :	1k~20k Hz
Voice Coil Diameter	音圈直径 :	44mm/1.7inch
Diaphragm Material	膜片材质 :	Titanium
Magnet	磁体 :	Φ115Ferrite Ring/H15mm



TS44P

Throat Diameter	喉口直径 :	25mm/1inch
Nominal Impedance	标称阻抗 :	8Ω
RMS Power Input	额定功率 :	60W
MAX Power Input	最大功率 :	120W
Sensitivity 1W/1M	灵敏度 :	108.5dB
Frequency Range	频响范围 :	700~18k Hz
Voice Coil Diameter	音圈直径 :	44mm/1.7inch
Diaphragm Material	膜片材质 :	HT Polymer
Magnet	磁体 :	Φ120Ferrite Ring/H20mm



MR440F

Throat Diameter	喉口直径 :	25mm/1 inch
Nominal Impedance	标称阻抗 :	8Ω
RMS Power Input	额定功率 :	60W
MAX Power Input	最大功率 :	120W
Sensitivity 1W/1M	灵敏度 :	104dB
Frequency Range	频响范围 :	800~19k Hz
Voice Coil Diameter	音圈直径 :	44mm/1.7 inch
Diaphragm Material	膜片材质 :	HT Polymer
Magnet	磁体 :	Φ115Ferrite Ring/H15mm



MR3408L

Throat Diameter	喉口直径 :	25mm/1 inch
Nominal Impedance	标称阻抗 :	8Ω
RMS Power Input	额定功率 :	50W
MAX Power Input	最大功率 :	100W
Sensitivity 1W/1M	灵敏度 :	103dB
Frequency Range	频响范围 :	1~20k Hz
Voice Coil Diameter	音圈直径 :	34mm/1.4inch
Diaphragm Material	膜片材质 :	Titanium
Magnet	磁体 :	Φ90Ferrite Ring/H15mm



MR3408P1

Throat Diameter	喉口直径 :	25mm/1 inch
Nominal Impedance	标称阻抗 :	8Ω
RMS Power Input	额定功率 :	50W
MAX Power Input	最大功率 :	100W
Sensitivity 1W/1M	灵敏度 :	103dB
Frequency Range	频响范围 :	1~20k Hz
Voice Coil Diameter	音圈直径 :	34mm/1.4inch
Diaphragm Material	膜片材质 :	Titanium
Magnet	磁体 :	Φ90Ferrite Ring/H15mm



MR4408

Throat Diameter	喉口直径 :	25mm/1 inch
Nominal Impedance	标称阻抗 :	8Ω
RMS Power Input	额定功率 :	60W
MAX Power Input	最大功率 :	120W
Sensitivity 1W/1M	灵敏度 :	104dB
Frequency Range	频响范围 :	1~20k Hz
Voice Coil Diameter	音圈直径 :	44mm/1.7inch
Diaphragm Material	膜片材质 :	Titanium
Magnet	磁体 :	Φ115Ferrite Ring/H15mm



MR440H5

Throat Diameter	喉口直径 :	25mm/1 inch
Nominal Impedance	标称阻抗 :	8Ω
RMS Power Input	额定功率 :	60W
MAX Power Input	最大功率 :	120W
Sensitivity 1W/1M	灵敏度 :	105dB
Frequency Range	频响范围 :	1.5~20k Hz
Voice Coil Diameter	音圈直径 :	44mm/1.7inch
Diaphragm Material	膜片材质 :	Titanium
Magnet	磁体 :	Φ115Ferrite Ring/H15mm



MR4408P1

Throat Diameter	喉口直径:	25mm/1 inch
Nominal Impedance	标称阻抗:	8Ω
RMS Power Input	额定功率:	60W
MAX Power Input	最大功率:	120W
Sensitivity 1W/1M	灵敏度:	107dB
Frequency Range	频响范围:	1.5~20k Hz
Voice Coil Diameter	音圈直径:	44mm/1.7inch
Diaphragm Material	膜片材质:	HT Polymer
Magnet	磁体:	Φ115Ferrite Ring/H15mm



MR4408L

Throat Diameter	喉口直径:	25mm/1 inch
Nominal Impedance	标称阻抗:	8Ω
RMS Power Input	额定功率:	60W
MAX Power Input	最大功率:	120W
Sensitivity 1W/1M	灵敏度:	106dB
Frequency Range	频响范围:	1.5K~20k Hz
Voice Coil Diameter	音圈直径:	44mm/1.7inch
Diaphragm Material	膜片材质:	Titanium
Magnet	磁体:	Φ115Ferrite Ring/H15mm



MR4415

Throat Diameter	喉口直径:	27mm/1.1inch
Nominal Impedance	标称阻抗:	16Ω
RMS Power Input	额定功率:	60W
MAX Power Input	最大功率:	120W
Sensitivity 1W/1M	灵敏度:	105dB
Frequency Range	频响范围:	700~18k Hz
Voice Coil Diameter	音圈直径:	44mm/1.7inch
Diaphragm Material	膜片材质:	HT Polymer
Magnet	磁体:	Φ126Ferrite Ring/H20mm



MR5108L

Throat Diameter	喉口直径:	25mm/1inch
Nominal Impedance	标称阻抗:	8Ω
RMS Power Input	额定功率:	80W
MAX Power Input	最大功率:	160W
Sensitivity 1W/1M	灵敏度:	106dB
Frequency Range	频响范围:	1~20k Hz
Voice Coil Diameter	音圈直径:	51mm/2inch
Diaphragm Material	膜片材质:	Titanium
Magnet	磁体:	Φ135Ferrite Ring/H15mm



MR5108P1

Throat Diameter	喉口直径:	25mm/1inch
Nominal Impedance	标称阻抗:	8Ω
RMS Power Input	额定功率:	70W
MAX Power Input	最大功率:	140W
Sensitivity 1W/1M	灵敏度:	107dB
Frequency Range	频响范围:	800~17k Hz
Voice Coil Diameter	音圈直径:	51mm/2inch
Diaphragm Material	膜片材质:	Titanium
Magnet	磁体:	Φ135Ferrite Ring/H15mm



MR510S1

Throat Diameter	喉口直径:	25mm/1inch
Nominal Impedance	标称阻抗:	8Ω
RMS Power Input	额定功率:	70W
MAX Power Input	最大功率:	140W
Sensitivity 1W/1M	灵敏度:	107dB
Frequency Range	频响范围:	800~17k Hz
Voice Coil Diameter	音圈直径:	51mm/2inch
Diaphragm Material	膜片材质:	Titanium
Magnet	磁体:	Φ135Ferrite Ring/H15mm



BH400

Throat Diameter	喉口直径:	25mm/1 inch
Nominal Impedance	标称阻抗:	8Ω
RMS Power Input	额定功率:	60W
MAX Power Input	最大功率:	120W
Sensitivity 1W/1M	灵敏度:	107dB
Frequency Range	频响范围:	1K~18k Hz
Voice Coil Diameter	音圈直径:	44mm/1.7inch
Diaphragm Material	膜片材质:	HT Polymer
Magnet	磁体:	Neodymium Ring



BH800

Throat Diameter	喉口直径:	38mm/1.5 inch
Nominal Impedance	标称阻抗:	8Ω
RMS Power Input	额定功率:	110W
MAX Power Input	最大功率:	220W
Sensitivity 1W/1M	灵敏度:	109dB
Frequency Range	频响范围:	600~18k Hz
Voice Coil Diameter	音圈直径:	75mm/3inch
Diaphragm Material	膜片材质:	Titanium
Magnet	磁体:	Neodymium Ring



MR51-1

Throat Diameter	喉口直径:	25mm/1inch
Nominal Impedance	标称阻抗:	8Ω
RMS Power Input	额定功率:	70W
MAX Power Input	最大功率:	140W
Sensitivity 1W/1M	灵敏度:	108dB
Frequency Range	频响范围:	800~17k Hz
Voice Coil Diameter	音圈直径:	51mm/2inch
Diaphragm Material	膜片材质:	Titanium
Magnet	磁体:	Φ135Ferrite Ring/H15mm



MR51-5

Throat Diameter	喉口直径:	25mm/1inch
Nominal Impedance	标称阻抗:	8Ω
RMS Power Input	额定功率:	70W
MAX Power Input	最大功率:	140W
Sensitivity 1W/1M	灵敏度:	107dB
Frequency Range	频响范围:	1.3k~17k Hz
Voice Coil Diameter	音圈直径:	51mm/2inch
Diaphragm Material	膜片材质:	Titanium
Magnet	磁体:	Φ135Ferrite Ring/H15mm



MR72-6

Throat Diameter	喉口直径:	50mm/2 inch
Nominal Impedance	标称阻抗:	8Ω
RMS Power Input	额定功率:	110W
MAX Power Input	最大功率:	220W
Sensitivity 1W/1M	灵敏度:	104dB
Frequency Range	频响范围:	600~20k Hz
Voice Coil Diameter	音圈直径:	72mm/2.5inch
Diaphragm Material	膜片材质:	Titanium
Magnet	磁体:	Φ170Ferrite Ring/H20mm



MR44XT

Throat Diameter	喉口直径:	50mm /2 inch
Nominal Impedance	标称阻抗:	8Ω
RMS Power Input	额定功率:	80W
MAX Power Input	最大功率:	160W
Sensitivity 1W/1M	灵敏度:	105dB
Frequency Range	频响范围:	400~20k Hz
Voice Coil Diameter	音圈直径:	100mm/4inch
Diaphragm Material	膜片材质:	Titanium
Magnet	磁体:	Φ220Ferrite Ring/H20mm



MR44-25A

Throat Diameter	喉口直径：	25mm/1inch
Nominal Impedance	标称阻抗：	8Ω
RMS Power Input	额定功率：	50W
MAX Power Input	最大功率：	100W
Sensitivity 1W/1M	灵敏度：	108dB
Frequency Range	频响范围：	800-18k Hz
Voice Coil Diameter	音圈直径：	44mm/1.7inch
Diaphragm Material	膜片材质：	Polyester
Magnet	磁体：	Φ120Ferrite Ring/H15mm



MR44-25

Throat Diameter	25mm/1inch
Nominal Impedance	8Ω
RMS Power Input	50W
MAX Power Input	100W
Sensitivity 1W/1M	109dB
Frequency Range	700-18k Hz
Voice Coil Diameter	44mm/1.7inch
Diaphragm Material	Polyester
Magnet	Φ135Ferrite Ring/H15mm



MR850

Throat Diameter	50mm/2 inch
Nominal Impedance	8Ω
RMS Power Input	110W
MAX Power Input	220W
Sensitivity 1W/1M	108.5dB
Frequency Range	600-18k Hz
Voice Coil Diameter	75mm/3 inch
Diaphragm Material	Titanium
Magnet	Φ180Ferrite Ring/H20mm



MR350

Throat Diameter	喉口直径：	25mm/1inch
Nominal Impedance	标称阻抗：	8Ω
RMS Power Input	额定功率：	60W
MAX Power Input	最大功率：	120W
Sensitivity 1W/1M	灵敏度：	104dB
Frequency Range	频响范围：	1-20k Hz
Voice Coil Diameter	音圈直径：	44mm/1.7inch
Diaphragm Material	膜片材质：	Titanium
Magnet	磁体：	Neodymium Ring



MR650N

Throat Diameter	35mm/1.39inch
Nominal Impedance	8Ω
RMS Power Input	90W
MAX Power Input	180W
Sensitivity 1W/1M	108dB
Frequency Range	600-20k Hz
Voice Coil Diameter	63.7mm/2.5inch
Diaphragm Material	Titanium
Magnet	Neodymium Ring



MR44T08N

Throat Diameter	25mm/1inch
Nominal Impedance	8Ω
RMS Power Input	60W
MAX Power Input	120W
Sensitivity 1W/1M	106dB
Frequency Range	1k-18k Hz
Voice Coil Diameter	44mm/1.7inch
Diaphragm Material	Titanium
Magnet	Neodymium Ring



MR65T08N

Throat Diameter	喉口直径：	36mm/1.4inch
Nominal Impedance	标称阻抗：	8Ω
RMS Power Input	额定功率：	90W
MAX Power Input	最大功率：	180W
Sensitivity 1W/1M	灵敏度：	108dB
Frequency Range	频响范围：	600~18k Hz
Voice Coil Diameter	音圈直径：	65mm/2.5inch
Diaphragm Material	膜片材质：	Titanium
Magnet	磁体：	Neodymium Ring



MR464

Throat Diameter	36mm/1.4inch
Nominal Impedance	8Ω
RMS Power Input	TW:80W/MID:110W
MAX Power Input	TW:160W/MID:220W
Sensitivity 1W/1M	113dB
Frequency Range	TW:3.5k-18kHz / MID:300-5.5kHz
Voice Coil Diameter	TW:65mm / MID:100mm
Diaphragm Material	HT-Polye
Magnet	Neodymium Ring



MR8901

Throat Diameter	50mm/2inch
Nominal Impedance	8Ω
RMS Power Input	TW:60W/MID:80W
MAX Power Input	TW:120W/MID:160W
Sensitivity 1W/1M	108dB
Frequency Range	MID:400-8kHz/TW:6k-20kHz
Voice Coil Diameter	TW:44mm / MID:89mm
Diaphragm Material	POLYE
Magnet	Neodymium Ring



MR8902

Throat Diameter	喉口直径：	50mm/2inch
Nominal Impedance	标称阻抗：	8Ω
RMS Power Input	额定功率：	160W
MAX Power Input	最大功率：	320W
Sensitivity 1W/1M	灵敏度：	109dB
Frequency Range	频响范围：	330-6k Hz
Voice Coil Diameter	音圈直径：	89mm/3.5inch
Diaphragm Material	膜片材质：	POLYE
Magnet	磁体：	Neodymium Ring



MR8903

Throat Diameter	50mm/2inch
Nominal Impedance	8Ω
RMS Power Input	80W
MAX Power Input	160W
Sensitivity 1W/1M	109dB
Frequency Range	400-8k Hz
Voice Coil Diameter	89mm/3.5inch
Diaphragm Material	POLYE
Magnet	Φ180Ferrite Ring/H20mm



MR8905

Throat Diameter	36mm/1.4inch
Nominal Impedance	8Ω
RMS Power Input	TW:60W/MID:80W
MAX Power Input	TW:120W/MID:160W
Sensitivity 1W/1M	110dB
Frequency Range	TW:8k-20kHz/TW:6k-20kHz
Voice Coil Diameter	TW:44mm / MID:89mm
Diaphragm Material	POLYE
Magnet	Neodymium Ring



MR44T50A-A

Throat Diameter	喉口直径:	25mm/1 inch
Nominal Impedance	标称阻抗:	8Ω
RMS Power Input	额定功率:	60W
MAX Power Input	最大功率:	120W
Sensitivity 1W/1M	灵敏度:	104dB
Frequency Range	频响范围:	950-20k Hz
Voice Coil Diameter	音圈直径:	44mm/1.7inch
Diaphragm Material	膜片材质:	Titanium
Magnet	磁体:	Φ115Ferrite Ring/H20mm



MR44-2

Throat Diameter	25mm/1 inch
Nominal Impedance	8Ω
RMS Power Input	60W
MAX Power Input	120W
Sensitivity 1W/1M	107dB
Frequency Range	900-18k Hz
Voice Coil Diameter	44mm/1.7inch
Diaphragm Material	HT Polymer
Magnet	Φ120Ferrite Ring/H18mm



MR44-3

Throat Diameter	25mm/1inch
Nominal Impedance	8Ω
RMS Power Input	60W
MAX Power Input	120W
Sensitivity 1W/1M	103.3dB
Frequency Range	700-18k Hz
Voice Coil Diameter	44mm/1.7inch
Diaphragm Material	HT Polymer
Magnet	Φ102Ferrite Ring/H18mm



MR4552

Throat Diameter	喉口直径:	25mm/1inch
Nominal Impedance	标称阻抗:	8Ω
RMS Power Input	额定功率:	80W
MAX Power Input	最大功率:	160W
Sensitivity 1W/1M	灵敏度:	113dB
Frequency Range	频响范围:	500~20k Hz
Voice Coil Diameter	音圈直径:	44mm/1.7inch
Diaphragm Material	膜片材质:	Polyester
Magnet	磁体:	Neodymium Ring



MR160-8

Throat Diameter	25mm/1inch
Nominal Impedance	8Ω
RMS Power Input	60W
MAX Power Input	120W
Sensitivity 1W/1M	107dB
Frequency Range	1.5K-18k Hz
Voice Coil Diameter	44mm/1.7inch
Diaphragm Material	HT Polymer
Magnet	Φ102Ferrite Ring/H18mm



MR250-8

Throat Diameter	25mm/1inch
Nominal Impedance	8Ω
RMS Power Input	40W
MAX Power Input	80W
Sensitivity 1W/1M	106dB
Frequency Range	1.5K-18k Hz
Voice Coil Diameter	44mm/1.7inch
Diaphragm Material	HT Polymer
Magnet	Φ120Ferrite Ring/H18mm



MR44T50A-H

Throat Diameter	喉口直径:	25mm/1 inch
Nominal Impedance	标称阻抗:	8Ω
RMS Power Input	额定功率:	60W
MAX Power Input	最大功率:	120W
Sensitivity 1W/1M	灵敏度:	103dB
Frequency Range	频响范围:	1k-18k Hz
Voice Coil Diameter	音圈直径:	44mm/1.7inch
Diaphragm Material	膜片材质:	Titanium
Magnet	磁体:	Φ115Ferrite Ring/H15mm



MR4410

Throat Diameter	25mm/1inch
Nominal Impedance	8Ω
RMS Power Input	80W
MAX Power Input	160W
Sensitivity 1W/1M	108dB
Frequency Range	700-17k Hz
Voice Coil Diameter	44mm/1.7inch
Diaphragm Material	Kapton
Magnet	Φ120Ferrite Ring/H15mm



MR610

Throat Diameter	38mm/1.5 inch
Nominal Impedance	8Ω
RMS Power Input	110W
MAX Power Input	220W
Sensitivity 1W/1M	109dB
Frequency Range	800-18k Hz
Voice Coil Diameter	65mm/2.5 inch
Diaphragm Material	Titanium
Magnet	Φ156Ferrite Ring/H20mm



MR75-13

Throat Diameter	喉口直径:	38mm/1.5inch
Nominal Impedance	标称阻抗:	8Ω
RMS Power Input	额定功率:	120W
MAX Power Input	最大功率:	240W
Sensitivity 1W/1M	灵敏度:	107.5dB
Frequency Range	频响范围:	500-18k Hz
Voice Coil Diameter	音圈直径:	75mm/3inch
Diaphragm Material	膜片材质:	Titanium
Magnet	磁体:	Φ170Ferrite Ring/H20mm



MR75-13D

Throat Diameter	38mm/1.5inch
Nominal Impedance	8Ω
RMS Power Input	120W
MAX Power Input	240W
Sensitivity 1W/1M	107.5dB
Frequency Range	500-18k Hz
Voice Coil Diameter	75mm/3inch
Diaphragm Material	Titanium
Magnet	Φ170Ferrite Ring/H20mm



MR75-9

Throat Diameter	38mm/1.5inch
Nominal Impedance	8Ω
RMS Power Input	80W
MAX Power Input	160W
Sensitivity 1W/1M	107.5dB
Frequency Range	800-18k Hz
Voice Coil Diameter	75mm/3inch
Diaphragm Material	Titanium
Magnet	Φ170Ferrite Ring/H20mm



MR914

Throat Diameter	喉口直径：	36mm/1.4 inch
Nominal Impedance	标称阻抗：	8Ω
RMS Power Input	额定功率：	110W
MAX Power Input	最大功率：	220W
Sensitivity 1W/1M	灵敏度：	110dB
Frequency Range	频响范围：	900-18k Hz
Voice Coil Diameter	音圈直径：	75mm/3inch
Diaphragm Material	膜片材质：	Titanium
Magnet	磁体：	Neodymium Ring



MR3601

Throat Diameter	喉口直径：	25mm/1inch
Nominal Impedance	标称阻抗：	8Ω
RMS Power Input	额定功率：	30W
MAX Power Input	最大功率：	60W
Sensitivity 1W/1M	灵敏度：	109dB
Frequency Range	频响范围：	800-20k Hz
Voice Coil Diameter	音圈直径：	75mm/3inch
Diaphragm Material	膜片材质：	Polyester
Magnet	磁体：	Neodymium Ring



MR400-B

Throat Diameter	喉口直径：	25mm/1 inch
Nominal Impedance	标称阻抗：	8Ω
RMS Power Input	额定功率：	50W
MAX Power Input	最大功率：	100W
Sensitivity 1W/1M	灵敏度：	106dB
Frequency Range	频响范围：	1.2-18k Hz
Voice Coil Diameter	音圈直径：	44mm/1.7inch
Diaphragm Material	膜片材质：	Polyimide
Magnet	磁体：	Neodymium Ring



MR800C

Throat Diameter	喉口直径：	38mm/1.5 inch
Nominal Impedance	标称阻抗：	8Ω
RMS Power Input	额定功率：	110W
MAX Power Input	最大功率：	220W
Sensitivity 1W/1M	灵敏度：	109dB
Frequency Range	频响范围：	600-18k Hz
Voice Coil Diameter	音圈直径：	75mm/3inch
Diaphragm Material	膜片材质：	Titanium
Magnet	磁体：	Neodymium Ring



MR800

Throat Diameter	喉口直径：	38mm/1.5inch
Nominal Impedance	标称阻抗：	8Ω
RMS Power Input	额定功率：	110W
MAX Power Input	最大功率：	220W
Sensitivity 1W/1M	灵敏度：	107.5dB
Frequency Range	频响范围：	500-18k Hz
Voice Coil Diameter	音圈直径：	75mm/3inch
Diaphragm Material	膜片材质：	Polyester
Magnet	磁体：	Neodymium Ring



MR680

Throat Diameter	喉口直径：	36mm/1.4 inch
Nominal Impedance	标称阻抗：	8Ω
RMS Power Input	额定功率：	90W
MAX Power Input	最大功率：	180W
Sensitivity 1W/1M	灵敏度：	109dB
Frequency Range	频响范围：	1k-20kHz
Voice Coil Diameter	音圈直径：	65mm/2.5inch
Diaphragm Material	膜片材质：	Titanium
Magnet	磁体：	Neodymium Ring



MR75T08N

Throat Diameter	喉口直径：	38mm/1.5inch
Nominal Impedance	标称阻抗：	8Ω
RMS Power Input	额定功率：	110W
MAX Power Input	最大功率：	220W
Sensitivity 1W/1M	灵敏度：	108dB
Frequency Range	频响范围：	500-18k Hz
Voice Coil Diameter	音圈直径：	75mm/3inch
Diaphragm Material	膜片材质：	Titanium
Magnet	磁体：	Neodymium Ring



MR950C

Throat Diameter	喉口直径：	38mm/1.5 inch
Nominal Impedance	标称阻抗：	8Ω
RMS Power Input	额定功率：	110W
MAX Power Input	最大功率：	220W
Sensitivity 1W/1M	灵敏度：	105dB
Frequency Range	频响范围：	500-18k Hz
Voice Coil Diameter	音圈直径：	75mm/3inch
Diaphragm Material	膜片材质：	Titanium
Magnet	磁体：	Neodymium Ring



MR2432

Throat Diameter	喉口直径：	38mm/1.5inch
Nominal Impedance	标称阻抗：	4Ω
RMS Power Input	额定功率：	110W
MAX Power Input	最大功率：	220W
Sensitivity 1W/1M	灵敏度：	110dB
Frequency Range	频响范围：	850-20k Hz
Voice Coil Diameter	音圈直径：	76mm/3inch
Diaphragm Material	膜片材质：	Titanium
Magnet	磁体：	Neodymium Ring



MR2414

Throat Diameter	喉口直径：	25mm/1inch
Nominal Impedance	标称阻抗：	8Ω
RMS Power Input	额定功率：	25W
MAX Power Input	最大功率：	50W
Sensitivity 1W/1M	灵敏度：	108dB
Frequency Range	频响范围：	1.3k-20k Hz
Voice Coil Diameter	音圈直径：	25mm/1inch
Diaphragm Material	膜片材质：	PET
Magnet	磁体：	Neodymium Ring



MR2408-1

Throat Diameter	喉口直径：	25mm/1inch
Nominal Impedance	标称阻抗：	8Ω
RMS Power Input	额定功率：	30W
MAX Power Input	最大功率：	60W
Sensitivity 1W/1M	灵敏度：	109dB
Frequency Range	频响范围：	1.2-20k Hz
Voice Coil Diameter	音圈直径：	38mm/1.5inch
Diaphragm Material	膜片材质：	PET
Magnet	磁体：	Neodymium Ring



MR2408-2

Throat Diameter	喉口直径：	25mm/1inch
Nominal Impedance	标称阻抗：	8Ω
RMS Power Input	额定功率：	30W
MAX Power Input	最大功率：	60W
Sensitivity 1W/1M	灵敏度：	110dB
Frequency Range	频响范围：	1200-20k Hz
Voice Coil Diameter	音圈直径：	38mm/1.5inch
Diaphragm Material	膜片材质：	PEN
Magnet	磁体：	Neodymium Ring



Model 型号: **Φ34**
Diameter 直径: **34mm**
Material 材料: **CCAR**



Model 型号: **Φ35**
Diameter 直径: **35mm**
Material 材料: **CCAW**



Model 型号: **Φ44**
Diameter 直径: **44mm**
Material 材料: **CCAW**



Model 型号: **Φ35**
Diameter 直径: **35mm**
Material 材料: **CCAW**



Model 型号: **Φ44**
Diameter 直径: **44mm**
Material 材料: **CCAR**



Model 型号: **Φ51**
Diameter 直径: **51mm**
Material 材料: **CCAW**



Model 型号: **Φ72**
Diameter 直径: **72mm**
Material 材料: **CCAW**



Model 型号: **Φ74.5**
Diameter 直径: **74.5mm**
Material 材料: **CCAR**



Model 型号: **Φ102**
Diameter 直径: **102mm**
Material 材料: **CCAR**



Model 型号: **Φ75**
Diameter 直径: **75mm**
Material 材料: **CCAW**



Model 型号: **Φ100**
Diameter 直径: **100mm**
Material 材料: **CCAR**



Model 型号: **Φ100**
Diameter 直径: **100mm**
Material 材料: **EISV**



Model 型号: **Φ100**
Diameter 直径: **100mm**
Material 材料: **AISV**



Model 型号: **Φ114**
Diameter 直径: **114mm**
Material 材料: **PISV**



Model 型号: **Φ125**
Diameter 直径: **125mm**
Material 材料: **AISV**



Model 型号: **Φ125**
Diameter 直径: **125mm**
Material 材料: **AISV**



Model 型号: **Φ150**
Diameter 直径: **150mm**
Material 材料: **CCAW**

CROSSOVERS



Model 型号: **PA-2**
Power 功率: **400w**
Type 类型: **10inch**



Model 型号: **F-2A**
Power 功率: **500w**
Type 类型: **12inch**



Model 型号: **KP-6012**
Power 功率: **500w**
Type 类型: **12inch**



Model 型号: **AK-212**
Power 功率: **400w**
Type 类型: **12inch**



Model 型号: **PA-28T**
Power 功率: **800w**
Type 类型: **15inch**



Model 型号: **SRX-725**
Power 功率: **500w**
Type 类型: **15inch**

COMPRESSION DRIVER HORNS



Model 型号: **Mr5915**
Diameter 直径: **26mm**
Material 材料: **工塑**
Size 尺寸: **100x87x110**



Model 型号: **Mr5928**
Diameter 直径: **26mm**
Material 材料: **ABS**
Size 尺寸: **350x240x145**



Model 型号: **Mr5942**
Diameter 直径: **26mm**
Material 材料: **工塑**
Size 尺寸: **215x199x248**



Model 型号: **Mr5222**
Diameter 直径: **38mm**
Material 材料: **ABS**
Size 尺寸: **280x280x225**



Model 型号: **Mr5323**
Diameter 直径: **38mm**
Material 材料: **PU**
Size 尺寸: **440x278x238**



Model 型号: **Mr5933**
Diameter 直径: **26mm**
Material 材料: **工塑**
Size 尺寸: **255x190x230**



美睿（广东）音响器材有限公司
Meirui (Guangdong) Audio Equipment Co., Ltd.
Web: www.merryaudio.com
Email: ma888@merryaudio.com

